

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

APLISENS - APRE-2000G SMART DIFFERENTIAL PRESSURE SENSORS

APRE-2000G

Please see below for available options and technical



- Pressure range -100 mbar to 100 mbar
- Min range 0.2mbar
- Three body styles available
- ATEX version



PRODUCT DESCRIPTION

The Aplisens APRE-2000G Smart differential pressure transmitter is applicable to gases, to the measurements of their pressure, underpressure and differential pressure.

The ability to select the radical conversion characteristics also enables this differential pressure transmitter to be used in gas flow measurement systems using reduced pipes or other impeding elecments.

The APRE-2000G Smart uses HART protocol and the following metrological parameters can be configured through this:

- · Units of pressure
- Start and end-points of the set range
- Damping time constant
- Conversion characteristics (radical, inversion, user's non-linear characteristics)

And through the data interchange with the probe you can also:

- · Identify the transmitter
- Read the currently measured hydrostatic pressure value, output current and percenatge of measuring range

This smart differential pressure transmitter has an accuracy of 0.1%, with five standard measuring ranges to choose from and is also available in ATEX. Application examples:

- Blast pressure
- · Chimney draughts
- Furnace chambers
- Clean rooms

Please refer to the image below for ordering information.

;		

TECHNICAL DATA

Approvals	ATEX
Connection	M20x1.5, Hose connection 6 mm, 1/4 NPT
IP class	IP65, IP66, IP67
Material	Stainless steel AISI 304
Material of wetted parts	Stainless steel AISI 304
Pressure range max	100 mbar
Pressure range min	-100 mbar
Signal type	4-20 mA / Hart
Supply voltage dc max	36 V DC
Supply voltage dc min	7.5 V DC
Temperature of media from	-10 °C
Temperature of media to	70 °C