

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

071040241B002 0-10V, 0..400 bar, G1/4-E, M12

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- Outstanding repeatability




## PRODUCT DESCRIPTION

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

## **TECHNICAL DATA**

Burst pressure	2000 bar		
Connection	G1/4-E		
Electrical connection	M12x1 4-pole		
IP class	IP67		
Long term stability	±0.1% FS p.a.		
Material of body	Stainless steel 1.4305		
Material of wetted parts	Stainless steel 1.4305, Titanium		
Overpressure protection	1600 bar		
Pressure range max	400 bar		
Pressure range min	0 bar		
Pressure reference	Gauge		
Pressure rise	5 bar/ms		
Repeatability	±0.1% FS		
Response time	2 ms		
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27		
Signal type	0-10 V		
Supply voltage dc max	32 V DC		
Supply voltage dc min	12 V DC		
Temperature ambient from	-40 °C		
Temperature ambient to	100 °C		
Temperature error	±0.01% FS/°C		
Temperature of media from	-40 °C		
Temperature of media to	125 °C		
Weight	80 g		
Vibration resistance	20g: 42000 Hz sine wave, DIN EN 60068-2-6		





Sealing G 1/4 DN EN ISO 1179-2 (DN 352-11) form E	G1/4 DIN 3852-A		ST NPT 1/4
Thread code: 41	Thread code: 03	Thread code: 04	Thread code: 09
M 10x1 DIN 3552-A	7/16-20 UNF	9/16-18 UNF	Circle And
Thread code: 30	Thread code: 20	Thread code: 21	Thread code: 42



