



## SUCO - 0110/0111 PRESSURE SWITCH

IP67, IP6K9K

0110411281611

10..20 bar, G1/8, No, NBR, Deutsch DT04-2P

- Up to 42 V
- Deutsch DT04-2P integrated connector
- Six adjustment ranges from 0,1..1 bar to 50..150 bar
- Normally open or normally closed
- Overpressure safety of 300 bar or 600 bar



### PRODUCT DESCRIPTION

The 0110/0111 series pressure switch is part of the integrated connector range from SUCO offering high IP rating. Integrated Deutsch DT04-2P connector and a maximum voltage of 42V with normally open or normally closed contacts housed in a hex 24 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include automotive, mobile hydraulics, water applications and braking systems.

### TECHNICAL DATA

Adjustment range max	20 bar
Adjustment range min	10 bar
Approvals	CSA US, RoHS II
Contact rating max	4 A
Deviation max	±1,0
Electrical connection	2-pole Deutsch
Function	Normally open (SPST)
IP class	IP67, IP6K9K
Material membrane	NBR
Material of body	Zinc-plated steel
Material of wetted parts	Zinc-plated steel, NBR
Max switching frequency/min	200
Pressure max	300 bar

<b>Pressure range max</b>	20 bar
<b>Pressure range min</b>	10 bar
<b>Pressure type</b>	Relativt tryck
<b>Process connection</b>	1/8 BSP
<b>Temperature ambient from</b>	-20 °C
<b>Temperature ambient to</b>	80 °C
<b>Temperature of media from</b>	-40 °C
<b>Temperature of media to</b>	100 °C
<b>Weight</b>	90 g
<b>Voltage ac/dc max</b>	42 V
<b>Voltage ac/dc min</b>	10 V



**0110 / 0111**



**Deutsch  
DT04-2P**

IP67, IP6K9K

H ≈ 61 mm

