



## SUCO - 0118/0119 PRESSURE SWITCH

IP65, IPx4K

0118415281615

20..50 bar, G1/8, No, NBR, AMP Junior Timer®

- Up to 42 V
- AMP Junior Timer® integrated connector
- Six adjustment ranges from 0,1..1 bar to 50..150 bar
- Normally open or normally closed
- Overpressure safety of 300 bar or 600 bar



### PRODUCT DESCRIPTION

The 0118/0119 series pressure switch is part of the integrated connector range from SUCO offering high IP rating. Integrated AMP Junior Timer® connector and a maximum voltage of 42V with normally open or normally closed contacts housed in a hex 24 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include automotive, mobile hydraulics, water applications and braking systems.

### TECHNICAL DATA

|                             |                        |
|-----------------------------|------------------------|
| Adjustment range max        | 50 bar                 |
| Adjustment range min        | 20 bar                 |
| Approvals                   | CSA US, RoHS II        |
| Contact rating max          | 4 A                    |
| Deviation max               | ±2,0                   |
| Electrical connection       | AMP Junior Timer       |
| Function                    | Normally open (SPST)   |
| IP class                    | IP65, IPx4k            |
| Material membrane           | NBR                    |
| Material of body            | Zinc-plated steel      |
| Material of wetted parts    | Zinc-plated steel, NBR |
| Max switching frequency/min | 200                    |

|                                   |                     |
|-----------------------------------|---------------------|
| <b>Mechanical life expectancy</b> | 1 million exchanges |
| <b>Pressure max</b>               | 300 bar             |
| <b>Pressure range max</b>         | 50 bar              |
| <b>Pressure range min</b>         | 20 bar              |
| <b>Pressure type</b>              | Relativt tryck      |
| <b>Process connection</b>         | 1/8 BSP             |
| <b>Temperature ambient from</b>   | -20 °C              |
| <b>Temperature ambient to</b>     | 80 °C               |
| <b>Temperature of media from</b>  | -40 °C              |
| <b>Temperature of media to</b>    | 100 °C              |
| <b>Weight</b>                     | 90 g                |
| <b>Voltage ac/dc max</b>          | 42 V                |
| <b>Voltage ac/dc min</b>          | 10 V                |



**0118 / 0117**



**AMP  
Junior Timer®**

IP65, IPx4K

H ≈ 54 mm

