



SUCO - 0150 VACUUM SWITCH

Aluminium body

0150456154001

-100..950mbar, G1/8 female, CO, ECO, DIN, Aluminium

- Up to 250 V
- Connector included (DIN 43650/Form A)
- Adjustment range of 100..950 mbar (relative)
- Changeover (SPDT)
- Over pressure safety of 20 bar



PRODUCT DESCRIPTION

The SUCO 0150 Vacuum Switch is a rugged, mechanical pressure-differential switch built for vacuum duties ranging from approximately 100 mbar to 950 mbar, with a tolerance of ± 50 mbar. It features snap-action silver contacts and supports changeover (SPDT) switching rated up to 250 VAC/250 VDC—with current capabilities of 5 A AC and 3.5 A DC. The aluminium-bodied switch incorporates a DIN EN 175301-803-A (DIN 43650) connector, offering IP 65 protection when mated, and handles switching frequencies up to 200 cycles/min with a mechanical life expectancy of around one million cycles. It's highly durable, withstanding overpressure up to 20 bar (290 psi), strong vibration (10 g), shock (294 m/s²), and fast pressure changes up to 1 bar/ms.

In practical terms, the 0150 excels in industrial vacuum and low-pressure control systems such as medical suction units, air-handling equipment, chemical process vacuum loops, and vacuum packaging machinery. Its changeover contact allows for both alarm and control functions. On-site adjustment of the switch point via an M12 screw simplifies installation and commissioning. The aluminium housing and ECO seal material ensure compatibility with air, oils, greases, fuels, and gasoline. Stable long-term performance and robust protection make the 0150 a dependable component for harsh environments, including wall-mounted installations on compressor banks, vacuum pumps, and safety shut-off systems.

TECHNICAL DATA

Contact load max ac	5 A
Contact load max dc	0.25 A
Deviation max	± 50 mbar
Electrical connection	DIN EN 175301-803-A
Function	Changeover (SPDT)
IP class	IP65
Material membrane	ECO
Material of body	Aluminium
Material of wetted parts	Aluminium, ECO

Max switching frequency/min	200
Operating range max	950 mbar
Operating range min	100 mbar
Pressure range max	0.95 bar
Pressure range min	0.1 bar
Process connection	G1/8 female
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Temperature of media from	-20 °C
Temperature of media to	100 °C
Type Pressure Switch	Vacuum
Weight	270 g
Voltage ac/dc max	250 V
Voltage ac/dc min	10 V

