OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SUCO - 0165 ATEX PRESSURE SWITCH

ATEX rated

0165451141001
100..400 bar, G1/4 female, CO, NBR, 2m cable, Ex, Aluminium



- Gas protected zones 1 and 2
- Up to 250 V
- Five adjustment ranges from 1..6 bar to 100..400 bar
- Changeover (SPDT)
- Over pressure safety from 200 bar up to 600 bar

PRODUCT DESCRIPTION

The SUCO 0165 is an intrinsically safe, mechanical pressure switch engineered for explosive environments (ATEX Zone 1 & 2 gas atmospheres: Ex II 2G Ex d IIC T6/T5 X). Housed in robust anodised aluminium (30 mm A/F) with a PG9 cable gland and a 2 m cable, it delivers changeover (SPDT) switching with silver contacts, capable of handling up to 250 VAC or VDC at 1 A. Field-adjustable setpoint ranges span five bands, overpressure safety extends to 200 bar (diaphragm types) or up to 600 bar (piston types) with a typical differential of 10–30 %. Its design ensures precision under stress—switch stability remains tight (±0.5 bar nominal), and it withstands mechanical shock (294 m/s²), vibration (10 g), and fast pressure spikes up to 1 bar/ms, delivering up to 200 cycles per minute for about one million actuations.
The SUCO 0165 is ideal for safety-critical tasks in oil & gas, petrochemical, chemical processing, mills, refineries, and other hazardous workplaces. Its ability to be adjusted under pressure simplifies commissioning and maintenance in live systems, while the wide adjustment profile suits applications from low-pressure gas detection to high-pressure hydraulic safety interlocks. The aluminium housing and explosion-proof certification ensure reliable performance in flammable atmospheres, and its high overpressure capacity makes it invaluable for pump control, leak detection, pressure alarm systems, and compressor shut-off in intrinsically safe zones. Practical use includes monitoring pipeline pressure, triggering shutdowns in gas lines, and providing safety interlocks on hydraulic machinery in Zone 1/2 environments.


TECHNICAL DATA

Adjustment range min	100 bar
Adjustment range max	400 bar
Pressure max	600 bar
Function	Changeover (SPDT)
Electrical connection	Embedded 2m cable
IP class	IP65
Approvals	CSA US, Ex-d
Material of body	Aluminium
Material of wetted parts	Aluminium, NBR

Material membrane	NBR
Temperature of media from	-20 °C
Temperature of media to	80 °C
Contact load max ac	1 A
Contact load max dc	0.25 A
Voltage ac/dc max	250 V
Voltage ac/dc min	10 V
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Deviation max	±5,0-9,0
Max switching frequency/min	200
Process connection	G1/4 female
Weight	380 g

Type Pressure Switch	ATEX







Contact assignment:

○ 1 = white
● 2 = green
● 4 = brown

