



## SUCO 0530 ELECTRONIC PRESSURE SWITCH

053025241B002  
PNP output (High Side), NO, 0-250 Bar, G 1/4 – DIN  
EN ISO 1179-2, M12 - DIN EN 61076-2-101-A

- One switching output
- Stainless steel & titanium wetted parts
- Silicon-on-sapphire technology
- Factory set



### PRODUCT DESCRIPTION

The Suco high performance series of electronic pressure switches offers outstanding overpressure protection (up to 4x), long service life even under high pressure change rates whilst giving very low temperature error and excellent long-term stability. Using Silicon-on-sapphire technology for high reliability, EMC compatibility and accuracy there are five standard pressure ranges starting at 0-10 bar all the way up to 0-600 bar and a hysteresis of 0.2%-99.8%. Output option of PNP or NPN and the choice of normally open or normally closed with one switching output factory set (unadjustable by the user). The wetted parts are made of stainless steel and titanium in an all welded design ensuring excellent media compatibility with seven standard electrical connection options including Deutsch, DIN and M12 combined with eight standard thread type options.

Customer specific solutions are also available on request.

#### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

## TECHNICAL DATA

### GENERAL DATA

Adjustment range max	250 bar
Adjustment range min	0 bar
Electrical connection	M12x1
Process connection	1/4 BSP

<b>Function</b>	Normally open (SPST)
<b>Output</b>	PNP
<b>Burst pressure</b>	2000 bar
<b>Pressure max</b>	1000 bar

## TEMPERATURE & MATERIALS DATA


<b>Temperature of media from</b>	-40 °C
<b>Temperature of media to</b>	125 °C
<b>Temperature ambient from</b>	-40 °C
<b>Temperature ambient to</b>	100 °C
<b>Material of body</b>	Stainless steel 1.4305
<b>Material of wetted parts</b>	Stainless steel 1.4305, Titanium

## ADDITIONAL DATA



<b>Supply voltage dc max</b>	32 V DC
<b>Supply voltage dc min</b>	9.6 V DC
<b>Pressure rise</b>	≤ 5,000 bar/s
<b>Switching time</b>	< 2 ms
<b>Switching point adjustment range</b>	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
<b>Weight</b>	80 g

## SAFETY & APPROVALS

<b>IP class</b>	IP67
<b>Hysteresis</b>	2..99.8% of nominal pressure range (full scale), programmable at factory
<b>Shock resistance</b>	500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27
<b>Vibration resistance</b>	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
<b>EMC</b>	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
<b>Accuracy</b>	±0.5 % of adjustment range (Full scale) at room temperature
<b>Long term stability</b>	±0.1 % of adjustment range (full scale) per year
<b>Mechanical life expectancy</b>	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
<b>Repeatability</b>	±0.1 % full scale



<b>Pin 1</b>	Uv+
<b>Pin 2</b>	nc
<b>Pin 3</b>	Gnd
<b>Pin 4</b>	Out



Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

ISO 15170-A1-4.1

Order number: 001

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

AMP Superseal

Order number: 002

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 003

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 004

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 005

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 006

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 007

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 008

Thread code: 41

Thread code: 50

Thread code: 58

Thread code: 59

Thread code: 60

Thread code: 62


Thread code: 71

Thread code: 72



hex 22

Connection diagrams



Technical modifications and errors excepted.



Technical modifications and errors excepted.

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

ISO 15170-A1-4.1

Order number: 001

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

AMP Superseal

Order number: 002

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 003

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 004

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 005

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 006

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 007

Pin	Assignment
1	Uv+
2	nc
3	Gnd
4	Out

Order number: 008

Thread code: 41

Thread code: 50

Thread code: 58

Thread code: 59

Thread code: 60

Thread code: 62

Thread code: 71

Thread code: 72



hex 22

Connection diagrams



Technical modifications and errors excepted.



Technical modifications and errors excepted.