

## OEM Automatic Ltd

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

070525141B001 0.5-4.5V, 0..25 bar, G1/4-E, DIN

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- · Outstanding repeatability





## PRODUCT DESCRIPTION

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

## **TECHNICAL DATA**

Accuracy	±0.5% FS
Burst pressure	200 bar

Connection	G1/4-E
Electrical connection	DIN EN 175301-803-A
IP class	IP67
Long term stability	±0.1% FS p.a.
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium
Overpressure protection	100 bar
Pressure range max	25 bar
Pressure range min	0 bar
Pressure reference	Gauge
Pressure rise	5 bar/ms
Repeatability	±0.1% FS
Response time	2 ms
Response time Shock resistance	2 ms 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
·	
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Shock resistance Signal type	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27 0.5-4.5 V ratiometric
Shock resistance Signal type Supply voltage dc max	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC
Shock resistance Signal type Supply voltage dc max Supply voltage dc min	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC  5 V DC
Shock resistance Signal type Supply voltage dc max Supply voltage dc min Temperature ambient from	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC  5 V DC  -40 °C
Shock resistance Signal type Supply voltage dc max Supply voltage dc min Temperature ambient from Temperature ambient to	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC  5 V DC  -40 °C  100 °C
Shock resistance Signal type Supply voltage dc max Supply voltage dc min Temperature ambient from Temperature ambient to Temperature error	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC  5 V DC  -40 °C  100 °C  ±0.01% FS/°C
Shock resistance Signal type Supply voltage dc max Supply voltage dc min Temperature ambient from Temperature ambient to Temperature error Temperature of media from	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC  5 V DC  -40 °C  ±0.01% FS/°C  -40 °C
Shock resistance  Signal type  Supply voltage dc max  Supply voltage dc min  Temperature ambient from  Temperature ambient to  Temperature error  Temperature of media from  Temperature of media to	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27  0.5-4.5 V ratiometric  6.5 V DC  5 V DC  -40 °C  100 °C  ±0.01% FS/°C  -40 °C  125 °C









