

## **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

070540141B001 0.5-4.5V, 0..40 bar, G1/4-E, DIN

- Measuring range up to 600 bar
- · Silicon-on-sapphire sensor
- Outstanding overpressure protection
- · Outstanding repeatability



## PRODUCT DESCRIPTION

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

## **TECHNICAL DATA**

| Accuracy       | ±0.5% FS |
|----------------|----------|
| Burst pressure | 320 bar  |

| Connection                | G1/4-E   |
|---------------------------|--|
| Electrical connection     | DIN EN 175301-803-A                                |
| IP class                  | IP67   |
| Long term stability       | ±0.1% FS p.a.                                      |
| Material of body          | Stainless steel 1.4305                             |
| Material of wetted parts  | Stainless steel 1.4305, Titanium                   |
| Overpressure protection   | 160 bar  |
| Pressure range max        | 40 bar   |
| Pressure range min        | 0 bar  |
| Pressure reference        | Gauge  |
| Pressure rise             | 5 bar/ms   |
| Repeatability             | ±0.1% FS   |
| Response time             | 2 ms   |
| Shock resistance          | 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27 |
| Signal type               | 0.5-4.5 V ratiometric                              |
| Supply voltage dc max     | 6.5 V DC   |
| Supply voltage dc min     | 5 V DC   |
| Temperature ambient from  | -40 °C   |
| Temperature ambient to    | 100 °C   |
| Temperature error         | ±0.01% FS/°C                                       |
| Temperature of media from | -40 °C   |
| Temperature of media to   | 125 °C   |
| Weight                    | 80 g   |
| Vibration resistance      | 20g: 42000 Hz sine wave, DIN EN 60068-2-6          |
|                           |  |









