

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SUCO - 0705/0710/0720 PRESSURE SENSOR

High performance series

072060141B001 4-20mA, 0..60 bar, G1/4-E, DIN

- Measuring range up to 600 bar
- Silicon-on-sapphire sensor
- Outstanding overpressure protection
- · Outstanding repeatability




PRODUCT DESCRIPTION

The SUCO 0705/0710/0720 high performance series pressure sensor is an advanced pressure monitoring solution with unrivalled attributes. Offering ten standard pressure ranges with options of six different electrical connectors a thread of G1/4 (eight available in total) and 0.5-4.5 V ratiomateric, 0-10V or 4-20mA outputs. The 07 series uses silicon-on-sapphire technology in a titanium all welded design offering outstanding overpressure protection, media compatibility and the highest repeatability.

Common applications include mobile hydraulics, off-shore/marine, high pressure systems and more.

TECHNICAL DATA

| Burst pressure | 480 bar | | |
|---------------------------|--|--|--|
| Connection | G1/4-E | | |
| Electrical connection | DIN EN 175301-803-A | | |
| IP class | IP67 | | |
| Long term stability | ±0.1% FS p.a. | | |
| Material of body | Stainless steel 1.4305 | | |
| Material of wetted parts | Stainless steel 1.4305, Titanium | | |
| Overpressure protection | 240 bar | | |
| Pressure range max | 60 bar | | |
| Pressure range min | 0 bar | | |
| Pressure reference | Gauge | | |
| Pressure rise | 5 bar/ms | | |
| Repeatability | ±0.1% FS | | |
| Response time | 2 ms | | |
| Shock resistance | 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27 | | |
| Signal type | 4-20 mA | | |
| Supply voltage dc max | 32 V DC | | |
| Supply voltage dc min | 10 V DC | | |
| Temperature ambient from | -40 °C | | |
| Temperature ambient to | 100 °C | | |
| Temperature error | ±0.01% FS/°C | | |
| Temperature of media from | -40 °C | | |
| Temperature of media to | 125 °C | | |
| Weight | 80 g | | |
| Vibration resistance | 20g: 42000 Hz sine wave, DIN EN 60068-2-6 | | |





| Sealing G 1/4 DN EN ISO 1179-2 (DN 352-11) form E | G1/4 DIN 3852-A | | ST NPT 1/4 |
|--|--------------------|-----------------|--|
| Thread code: 41 | Thread code: 03 | Thread code: 04 | Thread code: 09 |
| M 10x1 DIN 3552-A | 7/16-20 UNF | 9/16-18 UNF | Circle And |
| Thread code: 30 | Thread code: 20 | Thread code: 21 | Thread code: 42 |



