



## SUCO - 0114/0115 PRESSURE SWITCH

IP67

0114408282608

1..10 bar, G1/8, Nc, EPDM, Packard MetriPack 280®

- Up to 42 V
- Packard MetriPack 280® integrated connector
- Six adjustment ranges from 0,1..1 bar to 50..150 bar
- Normally open or normally closed
- Overpressure safety of 300 bar or 600 bar



### PRODUCT DESCRIPTION

The 0114/0115 series pressure switch is part of the integrated connector range from SUCO offering high IP rating. Integrated Packard MetriPack 280® connector and a maximum voltage of 42V with normally open or normally closed contacts housed in a hex 24 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include automotive, mobile hydraulics, water applications and braking systems.

### TECHNICAL DATA

Adjustment range max	10 bar
Adjustment range min	1 bar
Approvals	CSA US, RoHS II
Contact rating max	4 A
Deviation max	±0,5
Electrical connection	Packard MetriPack 280
Function	Normally Closed (SPST)
IP class	IP67
Material membrane	EPDM
Material of body	Zinc-plated steel
Material of wetted parts	EPDM, Zinc-plated steel
Max switching frequency/min	200

Pressure max	300 bar
Process connection	1/8 BSP
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Temperature of media from	-30 °C
Temperature of media to	120 °C
Weight	90 g
Voltage ac/dc max	42 V
Voltage ac/dc min	10 V



