OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

SUCO - 0180/0181 PRESSURE SWITCH

Long service life

0180457033003
0,3..1,5 bar, G1/4, CO, FKM, Spade



- Up to 250 V
- Spade terminals
- Five adjustment ranges from 0.3-1.5 bar to 50-200 bar
- Changeover (SPDT)
- Over pressure safety from 100 bar up to 600 bar

PRODUCT DESCRIPTION

The Suco 0180 (diaphragm) and 0181 (piston) switches are compact, high-performance mechanical pressure sensors housed in a zinc-plated steel (HEX 27 mm) body. Designed to handle up to 250 V AC/DC and up to 4 A resistive load via silver-contact SPDT switch, they are suited for challenging environments. Switching ranges span five field-adjustable bands, with factory-set hysteresis between 10–30 %. They offer strong overpressure resilience: diaphragm version withstands up to 400–700 bar, piston up to 700 bar . Environmental durability includes IP65 when paired with a socket, vibration tolerance to 10 g (5–200 Hz), shock resistance to 294 m/s², mechanical life up to 1 million cycles, and a switching frequency up to 200 per minute. Multiple process connections (G¼, ¼-18 BSPP, NPT, UNF, M10×1 taper, M12×1.5) and sealing options (NBR, EPDM, FKM, HNBR, FFKM) ensure compatibility with diverse media and temp ranges from –40 °C to +120 °C.
Practical and versatile, the 0180/0181 series is ideal for hydraulic powerpacks, mobile hydraulics, compressors, pneumatic controls, water systems, and general industrial pressure safety or control circuits. The diaphragm type better suits gaseous media and low-pressure ranges, while the piston variant excels in high-pressure hydraulic applications. Its quick-connect spade terminals (AMP 6.3 × 0.8 mm) and rugged steel housing offer fast installation and maintenance ,whether field-adjusted or factory preset, delivering stable, repeatable switching thresholds under high cycling and load. The Suco 0180/0181 stands out as a reliable, cost-effective solution for precise pressure threshold monitoring in tough real-world operations.

TECHNICAL DATA

Adjustment range min	0.3 bar
Adjustment range max	1.5 bar
Pressure max	100 bar
Function	Changeover (SPDT)
Electrical connection	Spade (AMP 6,3x0,8 mm)
IP class	IP00
Approvals	CSA US, RoHS II
Material of body	Galvanized steel
Material of wetted parts	FKM, Galvanized steel

Material membrane	FKM
Temperature of media from	-5 °C
Temperature of media to	120 °C
Contact load max ac	4 A
Contact load max dc	0.25 A
Voltage ac/dc max	250 V
Voltage ac/dc min	10 V
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Deviation max	±0,2
Max switching frequency/min	200
Process connection	1/4 BSP
Weight	100 g

Type Pressure Switch	High accuracy
Hysteresis	10-30% depending on set value
Mechanical life expectancy	1 million exchanges







