



SUCO - 0184/0185 PRESSURE SWITCH

IP65

0184461033012
10..100 bar, G1/4, CO, FKM, DIN

- Up to 250 V
- Connector included (DIN 43650/Form A)
- Five adjustment ranges from 0,3..1,5 bar to 50..200 bar
- Changeover (SPDT)
- Over pressure safety from 100 bar up to 600 bar



PRODUCT DESCRIPTION

The 0184/0185 series is part of the changeover contact range from SUCO with an integrated plastic body and connector. Offering a maximum voltage of 250 V with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include power packs, mobile hydraulics, water systems, hydraulics generally and pneumatics.

TECHNICAL DATA

Adjustment range max	100 bar
Adjustment range min	10 bar
Approvals	CSA US, RoHS II
Contact load max ac	4 A
Contact load max dc	0.25 A
Deviation max	±3,0-5,0
Electrical connection	DIN EN 175301-803-A
Function	Changeover (SPDT)
IP class	IP65
Material membrane	FKM
Material of body	Galvanized steel
Material of wetted parts	Galvanized steel, FKM

Max switching frequency/min	200
Pressure max	300 bar
Process connection	1/4 BSP
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Temperature of media from	-5 °C
Temperature of media to	120 °C
Type Pressure Switch	High accuracy
Weight	130 g
Voltage ac/dc max	250 V
Voltage ac/dc min	10 V



