



SUCO - 0132/0133 PRESSURE SWITCH

IP67

0133460033003

50..200 bar, G1/4, CO, FKM, TE AMP Superseal®

- Up to 48 V
- TE AMP Superseal 1.5® integrated connector
- Five adjustment ranges from 0,3..1,5 bar to 50..200 bar
- Changeover (SPDT)
- Over pressure safety from 100 bar up to 600 bar



PRODUCT DESCRIPTION




The 0132/0133 series pressure switch is part of the integrated connector range from SUCO offering high IP rating. Integrated TE AMP Superseal 1.5® connector and a maximum voltage of 48 V with a normally open and normally closed contact housed in a hex 27 zinc plated body offering a high pressure resistance. The switch point is very stable even after a long period of time and high load and is also adjustable on site and can come pre-set.

Common applications include automotive, mobile hydraulics, water applications and braking systems.

TECHNICAL DATA

Adjustment range max	200 bar
Adjustment range min	50 bar
Approvals	CSA US, RoHS II

Contact rating max	4 A
Deviation max	±5,0
Electrical connection	AMP Superseal
Function	Changeover (SPDT)
Hysteresis	10-30% depending on set value
IP class	IP67
Material membrane	FKM
Material of body	Zinc-plated steel
Material of wetted parts	FKM, Zinc-plated steel
Max switching frequency/min	200
Mechanical life expectancy	1 million exchanges
Pressure max	600 bar
Process connection	1/4 BSP
Shock resistance	294m / s ² ; 14 ms half sinusoidal wave; DIN EN 60068-2-27
Temperature ambient from	-20 °C
Temperature ambient to	80 °C
Temperature of media from	-15 °C
Temperature of media to	120 °C
Weight	100 g
Vibration resistance	10g: 5..200 Hz sine wave, DIN EN 60068-2-6
Voltage ac/dc max	48 V



0132 / 0133



TE AMP Superseal 1.5°
IP67

L ~ 73 mm

