

SUCO 0500/0501 ELECTRONIC PRESSURE SWITCH

Factory set

0500401412004
NO, 0 - 40 Bar, G 1/4, EPDM, 15170-A1-4.1

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing



PRODUCT DESCRIPTION

The SUCO 0500 and 0501 are compact, high-performance electronic pressure switches built around a ceramic thick-film sensor in a robust stainless steel (AISI 303) housing with a Hex-24 form factor. Factory-programmed with user-selectable switching points and hysteresis (2%–98%), these units feature a PNP high-side transistor output, with supply voltage ranging from 9.6–32 V DC and a maximum output current of 0.5 A (≤ 0.2 A above 50 °C). Pressure ranges span 0–2 to 0–250 bar, with overpressure resilience up to twice the nominal pressure and burst ratings up to 4×, depending on the model. They deliver rapid response, excellent accuracy, high repeatability, and long-term stability, while maintaining IP67 protection and resistance to vibration/shock in challenging environments. Advanced options include a USB PPD05 programming device for custom tuning of set points, hysteresis, delay, and window functions, and various connector/thread combinations (M12, DIN-43650, DT04, Superseal, cable).

The SUCO 0500/0501 series excels in precise pressure monitoring and safety control across hydraulics, mobile machinery, industrial automation, and process systems. Their high overpressure tolerance and rugged stainless-steel build ensure reliability in high-risk environments, while rapid response makes them ideal for pump protection, pressure interlock, and system shutdown scenarios. Ceramic sensors are chemically resistant, enabling use with hydraulic fluids, gases, and corrosive media. Programming flexibility allows for field customisation without mechanical intervention, a key advantage for OEMs and service teams requiring accurate, repeatable switching behaviour and reduced downtime.

TECHNICAL DATA

GENERAL DATA

Adjustment range max	40 bar
Adjustment range min	0 bar
Process connection	G1/4
Function	Normally open
Output	PNP
Burst pressure	140 bar
Pressure max	100 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-30 °C
Temperature of media to	125 °C
Temperature ambient from	-30 °C
Temperature ambient to	100 °C


Material of body	Stainless steel 1.4305
Material of wetted parts	EPDM, Stainless steel 1.4305
Material membrane	EPDM

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 1 bar/ms
Switching time	< 4 ms
Switching point adjustment range	3...100 % of adjustment range(full scale) nominal pressure, set at factory
Weight	80 g

SAFETY & APPROVALS

IP class	IP67, IP6K9K
Hysteresis	2...98% full scale, programmable at factory (maximum tolerance ±1.0% of adjustment range nominal pressure)
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	5,000,000 pulsations at rise rates to 1,000 bar/s nominal pressure
Repeatability	±0.1 % of adjustment range (full scale) nominal pressure



DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101-A	ISO 15770-A1-4-1																														
																																
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{bus}</td> </tr> <tr> <td>2</td> <td>Gnd</td> </tr> <tr> <td>3</td> <td>U_{bus}</td> </tr> <tr> <td>PE</td> <td>PE</td> </tr> </tbody> </table>	Pin	Assignment	1	U _{bus}	2	Gnd	3	U _{bus}	PE	PE	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{bus}</td> </tr> <tr> <td>2</td> <td>PE</td> </tr> <tr> <td>3</td> <td>Gnd</td> </tr> <tr> <td>4</td> <td>U_{bus}</td> </tr> </tbody> </table>	Pin	Assignment	1	U _{bus}	2	PE	3	Gnd	4	U _{bus}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{bus}</td> </tr> <tr> <td>2</td> <td>PE</td> </tr> <tr> <td>3</td> <td>Gnd</td> </tr> <tr> <td>4</td> <td>U_{bus}</td> </tr> </tbody> </table>	Pin	Assignment	1	U _{bus}	2	PE	3	Gnd	4	U _{bus}
Pin	Assignment																															
1	U _{bus}																															
2	Gnd																															
3	U _{bus}																															
PE	PE																															
Pin	Assignment																															
1	U _{bus}																															
2	PE																															
3	Gnd																															
4	U _{bus}																															
Pin	Assignment																															
1	U _{bus}																															
2	PE																															
3	Gnd																															
4	U _{bus}																															
<p>Ø10</p> <p>L = 60 mm without cable outlet L = 77 mm with cable outlet</p> <p>Order number: 015</p>	<p>Ø12</p> <p>L = 60 mm</p> <p>Order number: 002</p>	<p>Ø12.7 (Ø10.96)</p> <p>L = 50 mm</p> <p>Order number: 004</p>																														
<p>AMP Supersad 5.5*</p> 	<p>Deutsch DT04-BP</p> 	<p>Cable connection</p> 																														
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>U_{bus}</td> </tr> <tr> <td>2</td> <td>Gnd</td> </tr> <tr> <td>3</td> <td>U_{bus}</td> </tr> </tbody> </table>	Pin	Assignment	1	U _{bus}	2	Gnd	3	U _{bus}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>A</td> <td>U_{bus}</td> </tr> <tr> <td>B</td> <td>Gnd</td> </tr> <tr> <td>C</td> <td>U_{bus}</td> </tr> </tbody> </table>	Pin	Assignment	A	U _{bus}	B	Gnd	C	U _{bus}	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr> <td>red</td> <td>U_{bus}</td> </tr> <tr> <td>white</td> <td>U_{bus}</td> </tr> <tr> <td>black</td> <td>Gnd</td> </tr> </tbody> </table>	Pin	Assignment	red	U _{bus}	white	U _{bus}	black	Gnd						
Pin	Assignment																															
1	U _{bus}																															
2	Gnd																															
3	U _{bus}																															
Pin	Assignment																															
A	U _{bus}																															
B	Gnd																															
C	U _{bus}																															
Pin	Assignment																															
red	U _{bus}																															
white	U _{bus}																															
black	Gnd																															
<p>Ø10.7</p> <p>L = 61 mm</p> <p>Order number: 007</p>	<p>Ø12.7 (Ø10.96)</p> <p>L = 61 mm</p> <p>Order number: 010</p>	<p>Ø12.7</p> <p>L = 47 mm (+ 25 mm barrel outlet) Cable length: 2 m</p> <p>Order number: 011</p>																														
 <p>Thread code: 01</p>	 <p>Thread code: 02</p>																															



	no / nc
○ 1	(+)
○ 2	(GND)
○ 3	(OUT)

DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101-A	ISO 15770-A1-4-1																														
																																
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{bus}</td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>U_{bus}</td></tr><tr><td>PE</td><td>PE</td></tr></table>	Pin	Assignment	1	U _{bus}	2	Gnd	3	U _{bus}	PE	PE	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{bus}</td></tr><tr><td>2</td><td>PE</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>U_{bus}</td></tr></table>	Pin	Assignment	1	U _{bus}	2	PE	3	Gnd	4	U _{bus}	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{bus}</td></tr><tr><td>2</td><td>PE</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>U_{bus}</td></tr></table>	Pin	Assignment	1	U _{bus}	2	PE	3	Gnd	4	U _{bus}
Pin	Assignment																															
1	U _{bus}																															
2	Gnd																															
3	U _{bus}																															
PE	PE																															
Pin	Assignment																															
1	U _{bus}																															
2	PE																															
3	Gnd																															
4	U _{bus}																															
Pin	Assignment																															
1	U _{bus}																															
2	PE																															
3	Gnd																															
4	U _{bus}																															
Ø10 L = 60 mm without cable outlet L = 77 mm with cable outlet Order number: 015	Ø12 L = 60 mm Order number: 002	Ø12.7 (Ø10.96) L = 50 mm Order number: 004																														
AMP Supersad 5.5* 	Deutsch DT04-BP 	Cable connection 																														
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>U_{bus}</td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>U_{bus}</td></tr></table>	Pin	Assignment	1	U _{bus}	2	Gnd	3	U _{bus}	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>A</td><td>U_{bus}</td></tr><tr><td>B</td><td>Gnd</td></tr><tr><td>C</td><td>U_{bus}</td></tr></table>	Pin	Assignment	A	U _{bus}	B	Gnd	C	U _{bus}	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>red</td><td>U_{bus}</td></tr><tr><td>white</td><td>U_{bus}</td></tr><tr><td>black</td><td>Gnd</td></tr></table>	Pin	Assignment	red	U _{bus}	white	U _{bus}	black	Gnd						
Pin	Assignment																															
1	U _{bus}																															
2	Gnd																															
3	U _{bus}																															
Pin	Assignment																															
A	U _{bus}																															
B	Gnd																															
C	U _{bus}																															
Pin	Assignment																															
red	U _{bus}																															
white	U _{bus}																															
black	Gnd																															
Ø10.7 L = 61 mm Order number: 007	Ø12.7 (Ø10.96) L = 61 mm Order number: 010	Ø12.7 L = 47 mm (+ 25 mm barrel relief) Cable length: 2 m Order number: 011																														
 Thread code: 01	 Thread code: 02																															