



## SUCO 0500/0501 ELECTRONIC PRESSURE SWITCH

Factory set

0501401417004  
NC, 0 - 40 Bar, G 1/4, TPE, 15170-A1-4.1

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

### PRODUCT DESCRIPTION

The SUCO 0500/0501 performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes factory set (unadjustable by the user) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0.2 bar all the way up to 0..100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP transistor output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.

Customer specific solutions are also available on request.

#### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

## TECHNICAL DATA

### GENERAL DATA

Adjustment range max	40 bar
Adjustment range min	0 bar
Process connection	G1/4
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	140 bar
Pressure max	100 bar

### TEMPERATURE & MATERIALS DATA


Temperature of media from	-30 °C
Temperature of media to	110 °C
Temperature ambient from	-30 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	TPE, Stainless steel 1.4305
Material membrane	TPE

### ADDITIONAL DATA


Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 1 bar/ms
Switching time	< 4 ms
Switching point adjustment range	3...100 % of adjustment range(full scale) nominal pressure, set at factory
Weight	80 g

SAFETY & APPROVALS

IP class	IP67, IP6K9K
Hysteresis	2...98% full scale, programmable at factory (maximum tolerance ±1.0% of adjustment range nominal pressure)
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	5,000,000 pulsations at rise rates to 1,000 bar/s nominal pressure
Repeatability	±0.1 % of adjustment range (full scale) nominal pressure



 Pin Assignment: 1: V <sub>cc</sub> 2: GND 3: V <sub>out</sub> 4: PE IP67 • 60 mm without cable solder • 77 mm with cable solder Order number: 011	 Pin Assignment: 1: V <sub>cc</sub> 2: PE 3: GND 4: V <sub>out</sub> IP67 • 54 mm Order number: 002	 Pin Assignment: 1: V <sub>cc</sub> 2: PE 3: GND 4: V <sub>out</sub> IP67 • 54 mm Order number: 004
 Pin Assignment: 1: V <sub>cc</sub> 2: GND 3: V <sub>out</sub> IP67 • 61 mm Order number: 007	 Pin Assignment: A: V <sub>cc</sub> B: GND C: V <sub>out</sub> IP67 • 61 mm Order number: 010	 Pin Assignment: red: V <sub>cc</sub> white: GND black: V <sub>out</sub> IP67 • 47 mm (+ 25 mm band relief) Cable length: ~ 2 m Order number: 011
 Thread code: 41	 Thread code: 49	



 Pin Assignment: 1: V <sub>cc</sub> 2: GND 3: V <sub>out</sub> 4: PE IP67 • 60 mm without cable solder • 77 mm with cable solder Order number: 011	 Pin Assignment: 1: V <sub>cc</sub> 2: PE 3: GND 4: V <sub>out</sub> IP67 • 54 mm Order number: 002	 Pin Assignment: 1: V <sub>cc</sub> 2: PE 3: GND 4: V <sub>out</sub> IP67 • 54 mm Order number: 004
 Pin Assignment: 1: V <sub>cc</sub> 2: GND 3: V <sub>out</sub> IP67 • 61 mm Order number: 007	 Pin Assignment: A: V <sub>cc</sub> B: GND C: V <sub>out</sub> IP67 • 61 mm Order number: 010	 Pin Assignment: red: V <sub>cc</sub> white: GND black: V <sub>out</sub> IP67 • 47 mm (+ 25 mm band relief) Cable length: ~ 2 m Order number: 011
 Thread code: 41	 Thread code: 49	

