

SUCO 0510/0511 G1/4 ELECTRONIC PRESSURE SWITCH

Adjustable by user

0510252412010

NO, 0 - 250 Bar, G 1/4, EPDM, Deutsch DT04-3P

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing



PRODUCT DESCRIPTION

The SUCO 0510 (NO) and 0511 (NC) models are compact, user-adjustable electronic pressure switches in a robust stainless-steel housing, featuring a 1/4-inch G1/4 process connection. They incorporate a ceramic thick-film pressure sensor and PNP transistor output, operating on 9.6–32 VDC with built-in reverse-polarity and short-circuit protection. The adjustable switching range spans from 0–2 bar up to 0–250 bar, with default hysteresis between 2–98% of full scale, and an impressive accuracy of ± 0.5 % FS. Overpressure resilience is rated at 2× nominal range, and burst resistance reaches up to 500 bar. With <4 ms switching response, mechanical durability of 5 million cycles, IP65–IP67 protection (depending on connector), and EMC compliance, these switches excel in reliability and longevity.


These switches are ideal for hydraulic, pneumatic, and fluid monitoring applications where space is limited, but precision and adjustability are essential—think mobile hydraulics, industrial compressors, and OEM machinery. External set-screw enables easy field adjustment, while the broad connector options (DIN EN 175301, M12, Superseal, Deutsch) simplify integration into varied control systems. Users benefit from ceramic sensor stability, low temperature drift (~ 0.04 % FS/°C), and repeatability (± 0.1 %), making them suitable for tasks like pressure safety cut-offs, pump control, and system diagnostics.


TECHNICAL DATA

Adjustment range min	0 bar
Adjustment range max	250 bar
Pressure max	500 bar
Function	Normally open

Electrical connection	Deutsch DT04-3P
IP class	IP67, IP6K9K
Material of body	Stainless steel 1.4305
Material of wetted parts	EPDM, Stainless steel 1.4305
Material membrane	EPDM
Temperature of media from	-30 °C
Temperature of media to	125 °C
Temperature ambient from	-30 °C
Temperature ambient to	100 °C
Process connection	G1/4
Weight	80 g


Pressure rise	≤ 1 bar/ms
Switching point adjustment range	3...100 % of adjustment range(full scale), set at factory
Switching time	< 4 ms
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Repeatability	±0.1 % of adjustment range (full scale)
Output	PNP
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
Burst pressure	500 bar
EMC	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
Hysteresis	2...98% full scale, programmable at factory (maximum tolerance ±1.0% of adjustment range nominal pressure)
Mechanical life expectancy	5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure
Long term stability	±0.1 % of adjustment range (full scale) per year





DIN EN 175301-803-A	M 12 – DIN EN 61076-2-101-A	ISO 15170-A1-4-1
Pin Assignment 1 Vcc 2 Gnd 3 Mux PE PE	Pin Assignment 1 Vcc 2 Gnd 3 Mux PE PE	Pin Assignment 1 Vcc 2 Gnd 3 Mux PE PE
IP67 x = 60 mm without angle socket x = 77 mm with angle socket Order number: 013	IP67 x = 54 mm Order number: 002	IP67 IP68/IK x = 56 mm Order number: 004

AMP Superseal 1.5"	Deutsch DT04-3P
Pin Assignment 1 A 2 Gnd 3 Vcc PE PE	Pin Assignment 1 A 2 Gnd 3 Vcc PE PE
IP67 x = 60 mm Order number: 003	IP67 IP68/IK x = 60 mm Order number: 018



DIN EN 175301-803-A	M 12 – DIN EN 61076-2-101-A	ISO 15170-A1-4-1
Pin Assignment 1 Vcc 2 Gnd 3 Mux PE PE	Pin Assignment 1 Vcc 2 Gnd 3 Mux PE PE	Pin Assignment 1 Vcc 2 Gnd 3 Mux PE PE
IP67 x = 60 mm without angle socket x = 77 mm with angle socket Order number: 013	IP67 x = 54 mm Order number: 002	IP67 IP68/IK x = 56 mm Order number: 004

AMP Superseal 1.5"	Deutsch DT04-3P
Pin Assignment 1 A 2 Gnd 3 Vcc PE PE	Pin Assignment 1 A 2 Gnd 3 Vcc PE PE
IP67 x = 60 mm Order number: 003	IP67 IP68/IK x = 60 mm Order number: 018

