



## **SUCO 0510/0511 G1/4 ELECTRONIC PRESSURE SWITCH**

Adjustable by user

0511252417007

NC, 0 - 250 Bar, G 1/4, TPE, AMP Superseal 1.5

- Single switch point
- Small & compact
- Ceramic sensor
- Stainless steel housing

### **PRODUCT DESCRIPTION**

The SUCO performance series electronic pressure switch offers a small compact electronic switch without compromising on quality which comes adjustable by the user (hysteresis not adjustable) with overpressure protection (up to 2x), has a long service life and is also attractively priced especially at high volumes. Using a ceramic sensor in thick film technology for a good operating temperature range and accuracy, there are six standard pressure ranges starting from 0..2 bar all the way up to 0..100 bar and a hysteresis of 1%-98%, available in normally open or normally closed with a PNP output. The wetted parts are made of ceramic, stainless steel and either NBR, EPDM OR FKM ensuring excellent media compatibility, with six standard electrical connection options including Deutsch, DIN and M12 combined with two standard thread type options.

Customer specific solutions are also available on request.

#### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

## TECHNICAL DATA

### GENERAL DATA

|                       |                        |
|-----------------------|------------------------|
| Adjustment range max  | 250 bar                |
| Adjustment range min  | 0 bar                  |
| Electrical connection | AMP Superseal          |
| Process connection    | G1/4                   |
| Function              | Normally Closed (SPST) |
| Output                | PNP                    |
| Burst pressure        | 500 bar                |
| Pressure max          | 375 bar                |

### TEMPERATURE & MATERIALS DATA

|                           |                             |
|---------------------------|-----------------------------|
| Temperature of media from | -30 °C                      |
| Temperature of media to   | 110 °C                      |
| Temperature ambient from  | -30 °C                      |
| Temperature ambient to    | 100 °C                      |
| Material of body          | Stainless steel 1.4305      |
| Material of wetted parts  | TPE, Stainless steel 1.4305 |
| Material membrane         | TPE                         |

### ADDITIONAL DATA

|                                  |   |
|----------------------------------|---|
| Supply voltage dc max            | 32 V DC   |
| Supply voltage dc min            | 9.6 V DC  |
| Pressure rise                    | ≤ 1 bar/ms  |
| Switching time                   | < 4 ms  |
| Switching point adjustment range | 3...100 % of adjustment range(full scale), set at factory |

|        |      |
|--------|------|
| Weight | 80 g |
|--------|------|

## SAFETY & APPROVALS

|                            |  |
|----------------------------|--|
| IP class                   | IP67   |
| Hysteresis                 | 2...98% full scale, programmable at factory (maximum tolerance $\pm 1.0\%$ of adjustment range nominal pressure) |
| Shock resistance           | 500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27  |
| Vibration resistance       | 20g: 4..2000 Hz sine wave, DIN EN 60068-2-6  |
| EMC                        | EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007   |
| Accuracy                   | $\pm 0.5\%$ of adjustment range (Full scale) at room temperature   |
| Long term stability        | $\pm 0.1\%$ of adjustment range (full scale) per year  |
| Mechanical life expectancy | 5,000,000 pulsations at rise rates to 1 bar/ms nominal pressure  |
| Repeatability              | $\pm 0.1\%$ of adjustment range (full scale)   |



