



SUCO 0510/0511 NPT1/4 ELECTRONIC PRESSURE SWITCH

Adjustable by user

0510161091011

NO, 0 - 16 Bar, NPT 1/4, NBR, Cable connection

- Single Switch Point
- Small & Compact
- Ceramic Sensor
- Stainless Steel Housing

PRODUCT DESCRIPTION

The SUCO 0510/0511 series combines a compact stainless-steel (AISI 303) hex-24 housing with a high-performance ceramic thick-film sensor, offering exceptionally reliable, switchable pressure monitoring. Users can adjust the switching point and hysteresis on-site, covering ranges from just 0–2 bar up to 0–600 bar, with dual output configurations (NO or NC, PNP 500 mA capability), and visual LED status indication for easy diagnostics. They're designed to withstand overpressure of up to 2× rated pressure and meet IP67 protection when paired with sealed connectors. Installation versatility is further enhanced by an array of electrical (AMP Superseal, Deutsch, DIN, M12, cable) and process (¼-inch NPT, BSP, UNF, metric) connection options.

This series is ideal for OEM and industrial systems that require compact, field-adjustable pressure monitoring. It excels in hydraulic and pneumatic applications—such as construction equipment, material handling, and mobile machinery—where ruggedness and precision under harsh conditions are essential. The ceramic sensor resists corrosion and is unaffected by contact wear, making it suitable for systems with vibration, fluid contamination, or wash-down environments. With its PNP switching logic and adjustable hysteresis, it integrates smoothly into PLCs or relay-based controls for safety interlocks, pressure alarms, or automated shutdowns. Its robust overpressure tolerance and durable housing also make it a solid choice for mobile hydraulics and fluid processing where long-term reliability is critical.

TECHNICAL DATA

GENERAL DATA

| | |
|-----------------------|----------------------|
| Adjustment range max | 16 bar |
| Adjustment range min | 0 bar |
| Electrical connection | Embedded 2m cable |
| Process connection | 1/4 NPT |
| Function | Normally open (SPST) |
| Output | PNP |
| Burst pressure | 60 bar |
| Pressure max | 40 bar |

TEMPERATURE & MATERIALS DATA

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | Gnd |
| 3 | U _{ref} |
| 4 | U _{ref} |

IP67

Order number: 013

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | nc |
| 3 | Gnd |
| 4 | U _{ref} |

IP67

Order number: 002

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | nc |
| 3 | Gnd |
| 4 | U _{ref} |

IP67, IP68/9K

Order number: 004

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | Gnd |
| 3 | U _{ref} |

IP67

Order number: 007

| Pin | Assignment |
|-----|------------------|
| A | U _{ref} |
| B | Gnd |
| C | U _{ref} |

IP67, IP68/9K

Order number: 010

Thread code: 41

Thread code: 09



| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | Gnd |
| 3 | U _{ref} |
| 4 | U _{ref} |

IP67

Order number: 013

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | nc |
| 3 | Gnd |
| 4 | U _{ref} |

IP67

Order number: 002

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | nc |
| 3 | Gnd |
| 4 | U _{ref} |

IP67, IP68/9K

Order number: 004

| Pin | Assignment |
|-----|------------------|
| 1 | U _{ref} |
| 2 | Gnd |
| 3 | U _{ref} |

IP67

Order number: 007

| Pin | Assignment |
|-----|------------------|
| A | U _{ref} |
| B | Gnd |
| C | U _{ref} |

IP67, IP68/9K

Order number: 010

Thread code: 41

Thread code: 09