



SUCO - 0520 ELECTRONIC PRESSURE SWITCH

0520470413001

Normally Open, 0 – 10 bar, G 1/4 – DIN EN ISO 1179-2, FKM, DIN EN 175301-803-A

- Ceramic measuring cell
- Adjustable up to 250 bar
- High accuracy
- Adjustment by mechanical screw
- Overpressure proof up to 500 bar



PRODUCT DESCRIPTION

Compact electronic pressure switch in galvanized steel with a ceramic measuring cell for high accuracy. Very long lifetime and simple mechanical setting of switching point via potentiometer. Hysteresis adjustable from factory 2...95 % of working range.

TECHNICAL DATA

GENERAL DATA

Adjustment range max	10 bar
Adjustment range min	0 bar
Electrical connection	DIN EN 175301-803-A
Process connection	G1/4-E
Function	Normally open (SPST)
Output	PNP
Burst pressure	25 bar
Pressure max	20 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-20 °C
Temperature of media to	125 °C
Temperature ambient from	-30 °C
Temperature ambient to	80 °C

Material of body	Zinc-plated steel
Material of wetted parts	Zinc-plated steel, FKM
Material membrane	FKM

ADDITIONAL DATA

Supply voltage dc max	36 V DC
Supply voltage dc min	15 V DC
Pressure rise	≤ 1 bar/ms
Switching time	< 4 ms
Switching point adjustment range	2..100 % of adjustment range(full scale) nominal pressure, set from outside using set screw
Weight	240 g

SAFETY & APPROVALS

IP class	IP65
Hysteresis	2...95% full scale, programmable at factory (maximum tolerance $\pm 1.0\%$ of adjustment range nominal pressure)
Shock resistance	294m / s ² ; 14 ms half sinusoidal wave; DIN EN 60068-2-27
Vibration resistance	10g: 4-2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU; EN 61000-6-2:2005; EN 61000-6-3:2007
Accuracy	± 0.5 % of adjustment range (Full scale) at room temperature
Long term stability	± 0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	5,000,000 pulsations at rise rates to 1,000 bar/s nominal pressure
Repeatability	± 0.1 % of adjustment range (full scale) nominal pressure