



## SUCO 0530 ELECTRONIC PRESSURE SWITCH

053010109B002

PNP output (High Side), NO, 0-10 Bar, NPT 1/4, M12 -  
DIN EN 61076-2-101-A

- One switching output
- Stainless steel & titanium wetted parts
- Silicon-on-sapphire technology
- Factory set



### PRODUCT DESCRIPTION

The Suco high performance series of electronic pressure switches offers outstanding overpressure protection (up to 4x), long service life even under high pressure change rates whilst giving very low temperature error and excellent long-term stability. Using Silicon-on-sapphire technology for high reliability, EMC compatibility and accuracy there are five standard pressure ranges starting at 0-10 bar all the way up to 0-600 bar and a hysteresis of 0.2%-99.8%. Output option of PNP or NPN and the choice of normally open or normally closed with one switching output factory set (unadjustable by the user). The wetted parts are made of stainless steel and titanium in an all welded design ensuring excellent media compatibility with seven standard electrical connection options including Deutsch, DIN and M12 combined with eight standard thread type options.

Customer specific solutions are also available on request.

#### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

## TECHNICAL DATA

### GENERAL DATA

Adjustment range max	10 bar
Adjustment range min	0 bar
Electrical connection	M12x1
Process connection	1/4 NPT

<b>Function</b>	Normally open (SPST)
<b>Output</b>	PNP
<b>Burst pressure</b>	80 bar
<b>Pressure max</b>	40 bar

## TEMPERATURE & MATERIALS DATA

<b>Temperature of media from</b>	-40 °C
<b>Temperature of media to</b>	125 °C
<b>Temperature ambient from</b>	-40 °C
<b>Temperature ambient to</b>	100 °C
<b>Material of body</b>	Stainless steel 1.4305
<b>Material of wetted parts</b>	Stainless steel 1.4305, Titanium

## ADDITIONAL DATA

<b>Supply voltage dc max</b>	32 V DC
<b>Supply voltage dc min</b>	9.6 V DC
<b>Pressure rise</b>	≤ 5,000 bar/s
<b>Switching time</b>	< 2 ms
<b>Switching point adjustment range</b>	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
<b>Weight</b>	80 g

## SAFETY & APPROVALS

<b>IP class</b>	IP67
<b>Hysteresis</b>	2..99.8% of nominal pressure range (full scale), programmable at factory
<b>Shock resistance</b>	500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27
<b>Vibration resistance</b>	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
<b>EMC</b>	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
<b>Accuracy</b>	±0.5 % of adjustment range (Full scale) at room temperature
<b>Long term stability</b>	±0.1 % of adjustment range (full scale) per year
<b>Mechanical life expectancy</b>	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
<b>Repeatability</b>	±0.1 % full scale



DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15176-A1-4.1	AMP Superseal																																								
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Chn</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • 60 / 76 mm* • 10 mm <b>Order number: 001</b></p>	Pin	Assignment	1	Chn	2	Out	3	Out	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Chn</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • 54 mm • 10 mm <b>Order number: 002</b></p>	Pin	Assignment	1	Line	2	nc	3	Chn	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Chn</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • 65 mm • 10 mm <b>Order number: 004</b></p>	Pin	Assignment	1	Line	2	nc	3	Chn	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Chn</td></tr><tr><td>3</td><td>Line</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • 73 mm • 10 mm <b>Order number: 007</b></p>	Pin	Assignment	1	Out	2	Chn	3	Line	4	Out
Pin	Assignment																																										
1	Chn																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Chn																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Chn																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Chn																																										
3	Line																																										
4	Out																																										
*without cable (code = 0000), with cable (code = 10 mm)																																											
DEUTSCH DT04-4P																																											
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Chn</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Chn</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • 38 mm • 10 mm <b>Order number: 008</b></p>	Pin	Assignment	1	Chn	2	Out	3	Chn	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>A</td><td>Line</td></tr><tr><td>B</td><td>Chn</td></tr><tr><td>C</td><td>Out</td></tr></table> <p>IP67 • 38 mm • 10 mm <b>Order number: 010</b></p>	Pin	Assignment	A	Line	B	Chn	C	Out	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>Line</td></tr><tr><td>white</td><td>Out</td></tr><tr><td>black</td><td>Chn</td></tr></table> <p>IP67 • 64 mm (a 20 mm band add) cable length = 2 m • 10 mm <b>Order number: 011</b></p>		Cable	Assignment	red	Line	white	Out	black	Chn														
Pin	Assignment																																										
1	Chn																																										
2	Out																																										
3	Chn																																										
4	Out																																										
Pin	Assignment																																										
A	Line																																										
B	Chn																																										
C	Out																																										
Cable	Assignment																																										
red	Line																																										
white	Out																																										
black	Chn																																										
<b>Thread code 41</b>	<b>Thread code 03</b>	<b>Thread code 04</b>	<b>Thread code 09</b>																																								
<b>Thread code 00</b>	<b>Thread code 02</b>	<b>Thread code 21</b>	<b>Thread code 02</b>																																								



See 22

Connection diagrams



100 Ohm load



100 Ohm load

Technical modifications and errors excepted.

EN 175301-803-A	M 12 - EN 61076-2-101 A	ISO 15176-A1-4.1	AMP Superseal																																								
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Chn</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • <math>\Phi = 60 / 76 \text{ mm}^*</math> • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 001</b></p> <p><small>* without cable (extra) = 0 mm, with cable only = 75 mm</small></p>	Pin	Assignment	1	Chn	2	Out	3	Out	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Chn</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • <math>\Phi = 54 \text{ mm}</math> • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 002</b></p>	Pin	Assignment	1	Line	2	nc	3	Chn	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Chn</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • <math>\Phi = 65 \text{ mm}</math> • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 004</b></p>	Pin	Assignment	1	Line	2	nc	3	Chn	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Chn</td></tr><tr><td>3</td><td>Line</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • <math>\Phi = 73 \text{ mm}</math> • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 007</b></p>	Pin	Assignment	1	Out	2	Chn	3	Line	4	Out
Pin	Assignment																																										
1	Chn																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Chn																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Chn																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Chn																																										
3	Line																																										
4	Out																																										
<b>DEUTSCH DT04-4P</b>																																											
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Chn</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Chn</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 • <math>\Phi = 38 \text{ mm}</math> • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 008</b></p>	Pin	Assignment	1	Chn	2	Out	3	Chn	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>A</td><td>Line</td></tr><tr><td>B</td><td>Chn</td></tr><tr><td>C</td><td>Out</td></tr></table> <p>IP67 • <math>\Phi = 38 \text{ mm}</math> • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 010</b></p>	Pin	Assignment	A	Line	B	Chn	C	Out	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>Line</td></tr><tr><td>white</td><td>Out</td></tr><tr><td>black</td><td>Chn</td></tr></table> <p>IP67 • <math>\Phi = 64 \text{ mm}</math> (a 20 mm band add) cable length = 2 m • <math>\Phi = 10 \text{ mm}</math> <b>Order number: 011</b></p>		Cable	Assignment	red	Line	white	Out	black	Chn														
Pin	Assignment																																										
1	Chn																																										
2	Out																																										
3	Chn																																										
4	Out																																										
Pin	Assignment																																										
A	Line																																										
B	Chn																																										
C	Out																																										
Cable	Assignment																																										
red	Line																																										
white	Out																																										
black	Chn																																										
<b>Thread code 41</b>	<b>Thread code 03</b>	<b>Thread code 04</b>	<b>Thread code 09</b>																																								
<b>Thread code 00</b>	<b>Thread code 02</b>	<b>Thread code 21</b>	<b>Thread code 02</b>																																								



See 22

Connection diagrams



100 Ohm load



100 Ohm load

Technical modifications and errors excepted.