



SUCO 0530 ELECTRONIC PRESSURE SWITCH

053025109B004

PNP output (High Side), NO, 0-25 Bar, NPT 1/4,
Bayonet ISO 15170-A1-4.1

- One switching output
- Stainless steel & titanium wetted parts
- Silicon-on-sapphire technology
- Factory set



PRODUCT DESCRIPTION

The Suco high performance series of electronic pressure switches offers outstanding overpressure protection (up to 4x), long service life even under high pressure change rates whilst giving very low temperature error and excellent long-term stability. Using Silicon-on-sapphire technology for high reliability, EMC compatibility and accuracy there are five standard pressure ranges starting at 0-10 bar all the way up to 0-600 bar and a hysteresis of 0.2%-99.8%. Output option of PNP or NPN and the choice of normally open or normally closed with one switching output factory set (unadjustable by the user). The wetted parts are made of stainless steel and titanium in an all welded design ensuring excellent media compatibility with seven standard electrical connection options including Deutsch, DIN and M12 combined with eight standard thread type options.

Customer specific solutions are also available on request.

Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

TECHNICAL DATA

GENERAL DATA

Adjustment range max	25 bar
Adjustment range min	0 bar
Process connection	1/4 NPT
Function	Normally open (SPST)

Output	PNP
Burst pressure	200 bar
Pressure max	100 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	80 g

SAFETY & APPROVALS

IP class	IP67, IP6K9K
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale



DIN EN 175301-803-A  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 • $\Phi = 60 / 76 \text{ mm}^*$ • $\Phi = 10 / 10 \text{ mm}$ Order number: 001</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	M 12 - DIN EN 61076-2-101-A  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 • $\Phi = 54 \text{ mm}$ • $\Phi = 10 / 10 \text{ mm}$ Order number: 002</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	ISO 15176-A1-4-1  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 • $\Phi = 65 \text{ mm}$ • $\Phi = 10 / 10 \text{ mm}$ Order number: 003</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	AMP Superseal  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 • $\Phi = 73 \text{ mm}$ • $\Phi = 10 / 10 \text{ mm}$ Order number: 004</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
* without cable length = 0.5m, with cable length = 1.50m																																											
DEUTSCH DT04-4P  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 • $\Phi = 38 \text{ mm}$ • $\Phi = 10 / 10 \text{ mm}$ Order number: 005</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	DEUTSCH DT04-3P  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr></table> <p>IP67 • $\Phi = 38 \text{ mm}$ • $\Phi = 10 / 10 \text{ mm}$ Order number: 006</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	Cable connection  <table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>Ch+</td></tr><tr><td>white</td><td>Ch-</td></tr><tr><td>black</td><td>Ch0</td></tr><tr><td>black</td><td>Ch1</td></tr></table> <p>IP67 • $\Phi = 68 \text{ mm}$ • $\Phi = 20 \text{ mm}$ (cable length = 2 m) • $\Phi = 10 / 10 \text{ mm}$ Order number: 007</p>	Cable	Assignment	red	Ch+	white	Ch-	black	Ch0	black	Ch1													
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
Cable	Assignment																																										
red	Ch+																																										
white	Ch-																																										
black	Ch0																																										
black	Ch1																																										
 <p>Thread code 41 • $\Phi = 10 / 10 \text{ mm}$ Order number: 008</p>	 <p>Thread code 03 • $\Phi = 10 / 10 \text{ mm}$ Order number: 009</p>	 <p>Thread code 04 • $\Phi = 10 / 10 \text{ mm}$ Order number: 010</p>	 <p>Thread code 05 • $\Phi = 10 / 10 \text{ mm}$ Order number: 011</p>																																								
 <p>Thread code 06 • $\Phi = 10 / 10 \text{ mm}$ Order number: 012</p>	 <p>Thread code 07 • $\Phi = 10 / 10 \text{ mm}$ Order number: 013</p>	 <p>Thread code 08 • $\Phi = 10 / 10 \text{ mm}$ Order number: 014</p>	 <p>Thread code 09 • $\Phi = 10 / 10 \text{ mm}$ Order number: 015</p>																																								



Fig. 22

Connection diagrams



Fig. 23



Fig. 24

Technical modifications and errors excepted.

DIN EN 175301-803-A <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 Φ = 60 / 76 mm* Φ = 10 / 10 mm Order number: 001</p> <p>* without copper socket = 76 mm, with copper socket = 75 mm</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	M 12 - DIN EN 61076-2-101-A <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 Φ = 54 mm Φ = 10 / 10 mm Order number: 002</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	ISO 15176-A1-4-1 <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 Φ = 65 mm Φ = 10 / 10 mm Order number: 003</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	AMP Superseal <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 Φ = 73 mm Φ = 10 / 10 mm Order number: 004</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
DEUTSCH DT04-4P <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr><tr><td>4</td><td>Ch1</td></tr></table> <p>IP67 Φ = 38 mm Φ = 10 / 10 mm Order number: 005</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	4	Ch1	DEUTSCH DT04-3P <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Ch+</td></tr><tr><td>2</td><td>Ch-</td></tr><tr><td>3</td><td>Ch0</td></tr></table> <p>IP67 Φ = 38 mm Φ = 10 / 10 mm Order number: 006</p>	Pin	Assignment	1	Ch+	2	Ch-	3	Ch0	Cable connection <table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>Ch+</td></tr><tr><td>white</td><td>Ch-</td></tr><tr><td>black</td><td>Ch0</td></tr></table> <p>IP67 Φ = 68 mm Φ = 20 mm (cable length = 2 m) Φ = 10 / 10 mm Order number: 007</p>	Cable	Assignment	red	Ch+	white	Ch-	black	Ch0															
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
4	Ch1																																										
Pin	Assignment																																										
1	Ch+																																										
2	Ch-																																										
3	Ch0																																										
Cable	Assignment																																										
red	Ch+																																										
white	Ch-																																										
black	Ch0																																										
 Thread code 41 Φ = 10 / 10 mm Order number: 008	 Thread code 03 Φ = 10 / 10 mm Order number: 009	 Thread code 04 Φ = 10 / 10 mm Order number: 010	 Thread code 05 Φ = 10 / 10 mm Order number: 011																																								
 Thread code 06 Φ = 10 / 10 mm Order number: 012	 Thread code 07 Φ = 10 / 10 mm Order number: 013	 Thread code 08 Φ = 10 / 10 mm Order number: 014	 Thread code 09 Φ = 10 / 10 mm Order number: 015																																								



Fig. 22

Connection diagrams



Fig. 23



Fig. 24

Technical modifications and errors excepted.