



## SUCO 0530 ELECTRONIC PRESSURE SWITCH

053010209B013  
PNP output (High Side), NO, 0-100 Bar, NPT 1/4, DIN  
EN 175301-803-A

- One switching output
- Stainless steel & titanium wetted parts
- Silicon-on-sapphire technology
- Factory set



### PRODUCT DESCRIPTION

The Suco high performance series of electronic pressure switches offers outstanding overpressure protection (up to 4x), long service life even under high pressure change rates whilst giving very low temperature error and excellent long-term stability. Using Silicon-on-sapphire technology for high reliability, EMC compatibility and accuracy there are five standard pressure ranges starting at 0-10 bar all the way up to 0-600 bar and a hysteresis of 0.2%-99.8%. Output option of PNP or NPN and the choice of normally open or normally closed with one switching output factory set (unadjustable by the user). The wetted parts are made of stainless steel and titanium in an all welded design ensuring excellent media compatibility with seven standard electrical connection options including Deutsch, DIN and M12 combined with eight standard thread type options.

Customer specific solutions are also available on request.

#### Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

## TECHNICAL DATA

### GENERAL DATA

Adjustment range max	100 bar
Adjustment range min	0 bar
Electrical connection	DIN EN 175301-803-A
Process connection	1/4 NPT
Function	Normally open (SPST)

<b>Output</b>	PNP
<b>Burst pressure</b>	800 bar
<b>Pressure max</b>	400 bar

## TEMPERATURE & MATERIALS DATA


<b>Temperature of media from</b>	-40 °C
<b>Temperature of media to</b>	125 °C
<b>Temperature ambient from</b>	-40 °C
<b>Temperature ambient to</b>	100 °C
<b>Material of body</b>	Stainless steel 1.4305
<b>Material of wetted parts</b>	Stainless steel 1.4305, Titanium

## ADDITIONAL DATA

<b>Supply voltage dc max</b>	32 V DC
<b>Supply voltage dc min</b>	9.6 V DC
<b>Pressure rise</b>	≤ 5,000 bar/s
<b>Switching time</b>	< 2 ms
<b>Switching point adjustment range</b>	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
<b>Weight</b>	110 g

## SAFETY & APPROVALS


<b>IP class</b>	IP65
<b>Hysteresis</b>	2..99.8% of nominal pressure range (full scale), programmable at factory
<b>Shock resistance</b>	500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27
<b>Vibration resistance</b>	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
<b>EMC</b>	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
<b>Accuracy</b>	±0.5 % of adjustment range (Full scale) at room temperature
<b>Long term stability</b>	±0.1 % of adjustment range (full scale) per year
<b>Mechanical life expectancy</b>	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
<b>Repeatability</b>	±0.1 % full scale




<b>DIN EN 175301-803-A</b> <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Chn</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Φ = 60 / 76 mm Φ = 10 mm <b>Order number: 001</b></p>	Pin	Assignment	1	Chn	2	Out	3	Out	4	Out	<b>M 12 - DIN EN 61076-2-101-A</b> <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Φ = 54 mm Φ = 10 mm <b>Order number: 002</b></p>	Pin	Assignment	1	Line	2	nc	3	Out	4	Out	<b>ISO 15170-A1-4-1</b> <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67, IP68K Φ = 65 mm Φ = 10 mm <b>Order number: 005</b></p>	Pin	Assignment	1	Line	2	nc	3	Out	4	Out	<b>AMP Superseal</b> <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Φ = 73 mm Φ = 10 mm <b>Order number: 007</b></p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out
Pin	Assignment																																										
1	Chn																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
* without cable length = 2 m, with cable length = 1.50 m																																											
<b>DEUTSCH DT04-4P</b> <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Φ = 38 mm Φ = 10 mm <b>Order number: 008</b></p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out	<b>DEUTSCH DT04-3P</b> <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Φ = 38 mm Φ = 10 mm <b>Order number: 010</b></p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<b>Cable connection</b> <table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>Red</td><td>Line</td></tr><tr><td>White</td><td>Out</td></tr><tr><td>Black</td><td>Out</td></tr><tr><td>Green</td><td>Out</td></tr></table> <p>IP67 Φ = 64 mm 25 mm band width cable length = 2 m Φ = 10 mm <b>Order number: 011</b></p>	Cable	Assignment	Red	Line	White	Out	Black	Out	Green	Out											
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
Cable	Assignment																																										
Red	Line																																										
White	Out																																										
Black	Out																																										
Green	Out																																										
<p><b>Thread code 41</b></p>	<p><b>Thread code 03</b></p>	<p><b>Thread code 04</b></p>	<p><b>Thread code 09</b></p>																																								
<p><b>Thread code 05</b></p>	<p><b>Thread code 06</b></p>	<p><b>Thread code 21</b></p>	<p><b>Thread code 42</b></p>																																								



Connection diagrams



As programmed depending on each connector 100 Ohm for 100V




As programmed depending on each connector 100 Ohm for 100V

Technical modifications and errors excepted.

<b>DIN EN 175301-803-A</b>  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Chn</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Ø = 60 / 76 mm* Ø = 10 mm <b>Order number: 001</b></p> <p>* without cable section / 4 wires, with cable section / 5 wires</p>	Pin	Assignment	1	Chn	2	Out	3	Out	4	Out	<b>M 12 - DIN EN 61076-2-101-A</b>  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Ø = 54 mm Ø = 10 mm <b>Order number: 002</b></p>	Pin	Assignment	1	Line	2	nc	3	Out	4	Out	<b>ISO 15170-A1-4-1</b>  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>nc</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Ø = 65 mm Ø = 10 mm <b>Order number: 005</b></p>	Pin	Assignment	1	Line	2	nc	3	Out	4	Out	<b>AMP Superseal</b>  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Ø = 73 mm Ø = 10 mm <b>Order number: 007</b></p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out
Pin	Assignment																																										
1	Chn																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	nc																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
<b>DEUTSCH DT04-4P</b>  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Ø = 38 mm Ø = 10 mm <b>Order number: 008</b></p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out	<b>DEUTSCH DT04-3P</b>  <table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Line</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table> <p>IP67 Ø = 38 mm Ø = 10 mm <b>Order number: 010</b></p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<b>Cable connection</b>  <table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>Red</td><td>Line</td></tr><tr><td>White</td><td>Out</td></tr><tr><td>Black</td><td>Out</td></tr><tr><td>Green</td><td>Out</td></tr></table> <p>IP67 Ø = 64 mm (ø 25 mm band width) cable length = 2 m Ø = 10 mm <b>Order number: 011</b></p>	Cable	Assignment	Red	Line	White	Out	Black	Out	Green	Out											
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
Cable	Assignment																																										
Red	Line																																										
White	Out																																										
Black	Out																																										
Green	Out																																										
 <b>Thread code 41</b>	 <b>Thread code 03</b>	 <b>Thread code 04</b>	 <b>Thread code 09</b>																																								
 <b>Thread code 05</b>	 <b>Thread code 06</b>	 <b>Thread code 21</b>	 <b>Thread code 42</b>																																								



Connection diagrams



As programmed depending on each connector 100 Ohm for 100V



As programmed depending on each connector 100 Ohm for 100V

Technical modifications and errors excepted.