

SUCO 0530 ELECTRONIC PRESSURE SWITCH

053010242B008
PNP output (High Side), NO, 0-100 Bar, M14x1.5 – DIN
EN ISO 9974-2, Deutsch DT04-4P



- One switching output
- Stainless steel & titanium wetted parts
- Silicon-on-sapphire technology
- Factory set

PRODUCT DESCRIPTION

The SUCO 0530 is a high-performance electronic pressure switch featuring a rugged hex 22 stainless steel housing and titanium-wetted parts, designed for demanding environments. It uses a precision Silicon-on-Sapphire (SOS) sensing element for exceptional accuracy, low temperature drift, and long-term stability. This model provides a single PNP output with a “normally open” function, factory-set switching point and hysteresis, and high over-pressure protection to ensure safety under unexpected pressure spikes. It supports multiple pressure ranges up to 1,650 bar, thread options including G $\frac{1}{4}$, NPT, UNF, M10/M14, and electrical connector choices like Deutsch DT04, AMP Superseal, M12, bayonet, or pre-fitted cable, all rated to IP67/IP6K9K for water and dust resistance. Built for rugged industrial and mobile-hydraulic use, the 0530 excels in situations requiring reliable pressure monitoring under harsh conditions. Typical applications include hydraulic systems in construction machinery, mobile equipment, pneumatic systems, and even high-pressure applications in test benches or process lines. The SOS sensor ensures rapid detection and long-term measurement consistency, while the all-welded stainless steel/titanium design resists corrosion and eliminates elastomer seals, ideal for harsh media and high change-rate pressures. With robust connector choices and factory-set parameters, it offers plug-and-play integration, minimal setup, and reliable performance, making it a trusted choice for sectors like heavy machinery, off-road vehicles, marine hydraulics, and industrial automation.

TECHNICAL DATA

GENERAL DATA

Adjustment range max	100 bar
Adjustment range min	0 bar
Electrical connection	Deutsch DT04-4P
Process connection	M14x1.5
Function	Normally open
Output	PNP
Burst pressure	800 bar
Pressure max	400 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C

Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	80 g


SAFETY & APPROVALS

IP class	IP67, IP6K9K
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






Connection diagrams



For component depending on each connector
*0.072 dry for 0.04




For component depending on each connector
*0.072 dry for 0.04

Technical modifications and errors excepted.


DIN EN 175301-803-A	M 12 - DIN EN 51576-2-101 A	ISO 15170-A1-6.1	AMP Superseal																																								
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </tbody> </table> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 003</p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </tbody> </table> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 003</p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </tbody> </table> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 003</p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </tbody> </table> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 003</p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </tbody> </table> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 003</p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<table border="1"> <thead> <tr> <th>Pin</th> <th>Assignment</th> </tr> </thead> <tbody> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </tbody> </table> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 003</p>	Pin	Assignment	1	Line	2	Out	3	Out	4	Out	<p>Cable connection</p> <p>IP67, IP68/9K</p> <p>• 40 x 70 mm² • 12.5 mm • 12.5 mm Order number: 011</p>																					
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	Out																																										
3	Out																																										
4	Out																																										
<p>Thread code: 41</p>	<p>Thread code: 03</p>	<p>Thread code: 04</p>	<p>Thread code: 09</p>																																								
<p>Thread code: 00</p>	<p>Thread code: 00</p>	<p>Thread code: 01</p>	<p>Thread code: 02</p>																																								



Connection diagrams



For component depending on each connector
*0.072 dry for 0.04



For component depending on each connector
*0.072 dry for 0.04

Technical modifications and errors excepted.