



SUCO 0530 ELECTRONIC PRESSURE SWITCH

053025209B002
PNP output (High Side), NO, 0-250 Bar, NPT 1/4, M12 -
DIN EN 61076-2-101-A

- One switching output
- Stainless steel & titanium wetted parts
- Silicon-on-sapphire technology
- Factory set



PRODUCT DESCRIPTION

The Suco high performance series of electronic pressure switches offers outstanding overpressure protection (up to 4x), long service life even under high pressure change rates whilst giving very low temperature error and excellent long-term stability. Using Silicon-on-sapphire technology for high reliability, EMC compatibility and accuracy there are five standard pressure ranges starting at 0-10 bar all the way up to 0-600 bar and a hysteresis of 0.2%-99.8%. Output option of PNP or NPN and the choice of normally open or normally closed with one switching output factory set (unadjustable by the user). The wetted parts are made of stainless steel and titanium in an all welded design ensuring excellent media compatibility with seven standard electrical connection options including Deutsch, DIN and M12 combined with eight standard thread type options.

Customer specific solutions are also available on request.

Application examples

- Automotive
- Braking systems
- Medical
- Mobile hydraulics
- Off highway
- Off-shore
- Rail

TECHNICAL DATA

GENERAL DATA

Adjustment range max	250 bar
Adjustment range min	0 bar
Electrical connection	M12x1
Process connection	1/4 NPT

Function	Normally open (SPST)
Output	PNP
Burst pressure	2000 bar
Pressure max	1000 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	80 g

SAFETY & APPROVALS

IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale




DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15170-A1-4-1	AMP Superseal																																								
<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 60.75 mm • Ø 30 mm</p> <p>Order number: 001</p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • Ø 22 mm</p> <p>Order number: 002</p>	Pin	Assignment	1	Line	2	NC	3	Out	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 65 mm • Ø 27 mm</p> <p>Order number: 003</p>	Pin	Assignment	1	Line	2	NC	3	Out	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 73 mm • Ø 26 mm</p> <p>Order number: 007</p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	NC																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	NC																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
		Cable connection																																									
<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • Ø 22 mm</p> <p>Order number: 004</p>	Pin	Assignment	1	Out	2	Out	3	NC	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>A</td><td>Line</td></tr> <tr><td>B</td><td>Out</td></tr> <tr><td>C</td><td>Out</td></tr> <tr><td>D</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • Ø 22 mm</p> <p>Order number: 010</p>	Pin	Assignment	A	Line	B	Out	C	Out	D	Out	<table border="1"> <tr><th>Cable</th><th>Assignment</th></tr> <tr><td>red</td><td>Line</td></tr> <tr><td>white</td><td>Out</td></tr> <tr><td>black</td><td>Out</td></tr> <tr><td>black</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 44 mm (ø 20 mm band width) Cable length = 2 m</p> <p>• Ø 22 mm</p> <p>Order number: 011</p>		Cable	Assignment	red	Line	white	Out	black	Out	black	Out										
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	NC																																										
4	Out																																										
Pin	Assignment																																										
A	Line																																										
B	Out																																										
C	Out																																										
D	Out																																										
Cable	Assignment																																										
red	Line																																										
white	Out																																										
black	Out																																										
black	Out																																										



See 221


Connection diagram

See the blue file



Pin assignment depending on each connector

See the blue file



Pin assignment depending on each connector

See the blue file

Technical modifications and errors excepted.


DIN EN 175301-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15170-A1-4-1	AMP Superseal																																								
<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 60.75 mm • Ø 30 mm</p> <p>Order number: 001</p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • Ø 22 mm</p> <p>Order number: 002</p>	Pin	Assignment	1	Line	2	NC	3	Out	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 65 mm • Ø 27 mm</p> <p>Order number: 004</p>	Pin	Assignment	1	Line	2	NC	3	Out	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 73 mm • Ø 26 mm</p> <p>Order number: 007</p>	Pin	Assignment	1	Out	2	Out	3	Out	4	Out
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	NC																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Line																																										
2	NC																																										
3	Out																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	Out																																										
4	Out																																										
		Cable connection																																									
<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • Ø 22 mm</p> <p>Order number: 004</p>	Pin	Assignment	1	Out	2	Out	3	NC	4	Out	<table border="1"> <tr><th>Pin</th><th>Assignment</th></tr> <tr><td>A</td><td>Line</td></tr> <tr><td>B</td><td>Out</td></tr> <tr><td>C</td><td>Out</td></tr> <tr><td>D</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • Ø 22 mm</p> <p>Order number: 010</p>	Pin	Assignment	A	Line	B	Out	C	Out	D	Out	<table border="1"> <tr><th>Cable</th><th>Assignment</th></tr> <tr><td>red</td><td>Line</td></tr> <tr><td>white</td><td>Out</td></tr> <tr><td>black</td><td>Out</td></tr> <tr><td>black</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 44 mm (ø 20 mm band width) Cable length = 2 m</p> <p>• Ø 22 mm</p> <p>Order number: 011</p>		Cable	Assignment	red	Line	white	Out	black	Out	black	Out										
Pin	Assignment																																										
1	Out																																										
2	Out																																										
3	NC																																										
4	Out																																										
Pin	Assignment																																										
A	Line																																										
B	Out																																										
C	Out																																										
D	Out																																										
Cable	Assignment																																										
red	Line																																										
white	Out																																										
black	Out																																										
black	Out																																										



See 221


Connection diagram

See the blue file



Pin assignment depending on each connector

See the blue file



Pin assignment depending on each connector

See the blue file

Technical modifications and errors excepted.