



SUCO 0531 ELECTRONIC PRESSURE SWITCH

053110104B011

PNP output (High Side), NC, 0-10 Bar, NPT 1/8, Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	10 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	1/8 NPT
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	80 bar
Pressure max	40 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS

IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale



DIN EN 175305-803-A

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• = 10.0 mm

• = 10.0 mm

Order number: 001

M 12 - DIN EN 41576-2-101-A

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• = 10.0 mm

• = 10.0 mm

Order number: 002

ISO 15170-A1-A1

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• = 10.0 mm

• = 10.0 mm

Order number: 003

AMP Superseal

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• = 10.0 mm

• = 10.0 mm

Order number: 004

DEUTSCH DT04-4P

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• = 10.0 mm

• = 10.0 mm

Order number: 005

DEUTSCH DT04-3P

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl

PS

IP67

• = 10.0 mm

• = 10.0 mm

Order number: 006

Cable connection

• = 10.0 mm

• = 10.0 mm

Order number: 007

Thread code: 01

Thread code: 02

Thread code: 03

Thread code: 04

Thread code: 05

Thread code: 06

Thread code: 07

Thread code: 08


Thread code: 09

Thread code: 10




haz 221

Connection diagrams



Do not connect directly to each connector



Do not connect directly to each connector

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DN EN 61076-3-001 A	ISO 15715-A1-4-1	AMP Superseal																																						
<table><tr><td>Pin</td><td>Assignment</td></tr><tr><td>1</td><td>U_{ref}</td></tr><tr><td>2</td><td>in</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	U _{ref}	2	in	3	Out	4	Out	<table><tr><td>Pin</td><td>Assignment</td></tr><tr><td>1</td><td>U_{ref}</td></tr><tr><td>2</td><td>in</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	U _{ref}	2	in	3	Out	4	Out	<table><tr><td>Pin</td><td>Assignment</td></tr><tr><td>1</td><td>U_{ref}</td></tr><tr><td>2</td><td>in</td></tr><tr><td>3</td><td>Out</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	U _{ref}	2	in	3	Out	4	Out	<table><tr><td>Pin</td><td>Assignment</td></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>U_{ref}</td></tr></table>	Pin	Assignment	1	Out	2	Out	3	U _{ref}
Pin	Assignment																																								
1	U _{ref}																																								
2	in																																								
3	Out																																								
4	Out																																								
Pin	Assignment																																								
1	U _{ref}																																								
2	in																																								
3	Out																																								
4	Out																																								
Pin	Assignment																																								
1	U _{ref}																																								
2	in																																								
3	Out																																								
4	Out																																								
Pin	Assignment																																								
1	Out																																								
2	Out																																								
3	U _{ref}																																								
IP67	IP67	IP67	IP67																																						
Ø = 62 / 76 mm ^Ø	Ø = 54 mm	Ø = 65 mm	Ø = 73 mm																																						
Ø = 10 mm	Ø = 10 mm	Ø = 10 mm	Ø = 10 mm																																						
Order number: 001	Order number: 002	Order number: 004	Order number: 007																																						
*without cable (cable) = Ø 10mm, with cable (cable) = 5 mm																																									
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																																							
<table><tr><td>Pin</td><td>Assignment</td></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>U_{ref}</td></tr><tr><td>3</td><td>in</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	Out	2	U _{ref}	3	in	4	Out	<table><tr><td>Pin</td><td>Assignment</td></tr><tr><td>A</td><td>U_{ref}</td></tr><tr><td>B</td><td>Out</td></tr><tr><td>C</td><td>Out</td></tr></table>	Pin	Assignment	A	U _{ref}	B	Out	C	Out	<table><tr><td>Cable</td><td>Assignment</td></tr><tr><td>red</td><td>U_{ref}</td></tr><tr><td>white</td><td>Out</td></tr><tr><td>black</td><td>Out</td></tr></table>	Cable	Assignment	red	U _{ref}	white	Out	black	Out													
Pin	Assignment																																								
1	Out																																								
2	U _{ref}																																								
3	in																																								
4	Out																																								
Pin	Assignment																																								
A	U _{ref}																																								
B	Out																																								
C	Out																																								
Cable	Assignment																																								
red	U _{ref}																																								
white	Out																																								
black	Out																																								
IP67	IP67	IP67																																							
Ø = 38 mm	Ø = 38 mm	Ø = 64 mm																																							
Ø = 10 mm	Ø = 10 mm	Ø = 20 mm																																							
Order number: 008	Order number: 009	Order number: 011																																							
Thread code: 01	Thread code: 02	Thread code: 03	Thread code: 04																																						
Thread code: 05	Thread code: 06	Thread code: 07	Thread code: 08																																						
Thread code: 09	Thread code: 10	Thread code: 11	Thread code: 12																																						
Thread code: 13	Thread code: 14	Thread code: 15	Thread code: 16																																						
Thread code: 17	Thread code: 18	Thread code: 19	Thread code: 20																																						
Thread code: 21	Thread code: 22	Thread code: 23	Thread code: 24																																						
Thread code: 25	Thread code: 26	Thread code: 27	Thread code: 28																																						
Thread code: 29	Thread code: 30	Thread code: 31	Thread code: 32																																						