



SUCO 0531 ELECTRONIC PRESSURE SWITCH

053110109B013
PNP output (High Side), NC, 0-10 Bar, NPT 1/4, DIN
EN 175301-803-A

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	10 bar
Adjustment range min	0 bar
Electrical connection	DIN EN 175301-803-A
Process connection	1/4 NPT
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	80 bar
Pressure max	40 bar

TEMPERATURE & MATERIALS DATA



Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	110 g


SAFETY & APPROVALS

IP class	IP65
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale




Item 221

Connection diagrams







Pin assignment depending on each connection



Pin assignment depending on each connection

Technical modifications and errors excepted.


DIN EN 175301-803-A	M 12 - DIN EN 61076-2-103-A	ISO 15170-A1-K1	AMP Superseal																																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 60/7.76 mm² • D 30 mm</p> <p>Order number: 001 * without cable length = 0.0m, with cable length = 1.5m</p>	1	Out	2	Out	3	Out	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 27 mm</p> <p>Order number: 002 * without cable length = 0.0m, with cable length = 1.5m</p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 27 mm</p> <p>Order number: 004</p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 71 mm • D 28 mm</p> <p>Order number: 007</p>	1	Out	2	Out	3	Out	4	Out
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								

DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 21 mm</p> <p>Order number: 006</p>	1	Out	2	Out	3	NC	4	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 21 mm</p> <p>Order number: 010</p>	1	Line	2	Out	3	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>white</td></tr> <tr><td>3</td><td>black</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 68 mm to 20 mm bend radius cable length = 2 m • D 22 mm</p> <p>Order number: 011</p>	1	Line	2	white	3	black	4	Out
1	Out																							
2	Out																							
3	NC																							
4	Out																							
1	Line																							
2	Out																							
3	Out																							
1	Line																							
2	white																							
3	black																							
4	Out																							

 <p>Thread code: 01</p>	 <p>Thread code: 02</p>	 <p>Thread code: 03</p>	 <p>Thread code: 04</p>
 <p>Thread code: 05</p>	 <p>Thread code: 06</p>	 <p>Thread code: 07</p>	 <p>Thread code: 08</p>



hex 21







No pinout opening in each connector 10/20 key for 006



No pinout opening in each connector 10/20 key for 006

Technical modifications and errors excepted.

DIN EN 175301-803-A	M 12 - DIN EN 61076-2-103-A	ISO 15170-A1-K1	AMP Superseal																																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 60/7.76 mm² • D 30 mm</p> <p>Order number: 001 * without cable length = 0.0m, with cable length = 1.5m</p>	1	Out	2	Out	3	Out	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 27 mm</p> <p>Order number: 002 * without cable length = 0.0m, with cable length = 1.5m</p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 27 mm</p> <p>Order number: 004</p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 71 mm • D 28 mm</p> <p>Order number: 007</p>	1	Out	2	Out	3	Out	4	Out
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								

DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 21 mm</p> <p>Order number: 006</p>	1	Out	2	Out	3	NC	4	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 21 mm</p> <p>Order number: 010</p>	1	Line	2	Out	3	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>white</td></tr> <tr><td>3</td><td>black</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 68 mm to 20 mm bend radius cable length = 2 m • D 22 mm</p> <p>Order number: 011</p>	1	Line	2	white	3	black	4	Out
1	Out																							
2	Out																							
3	NC																							
4	Out																							
1	Line																							
2	Out																							
3	Out																							
1	Line																							
2	white																							
3	black																							
4	Out																							

 <p>Thread code: 01</p>	 <p>Thread code: 02</p>	 <p>Thread code: 03</p>	 <p>Thread code: 04</p>
 <p>Thread code: 05</p>	 <p>Thread code: 06</p>	 <p>Thread code: 07</p>	 <p>Thread code: 08</p>