



SUCO 0531 ELECTRONIC PRESSURE SWITCH

053110120B011
PNP output (High Side), NC, 0-10 Bar, 7/16 – 20 UNF,
Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	10 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	80 bar
Pressure max	40 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS


IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






haz 221

Connection diagrams



Do not connect directly to each connector
V_{CC} only to GND



Do not connect directly to each connector
V_{CC} only to GND

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DN EN 61076-3-001 A	ISO 15715-A1-4-1	AMP Superseal
Pin Assignment 1 VCC 2 Out 3 GND 4 Out IP67 Ø = 62 / 76 mm ^Ø Ø = 10 mm Order number: 000	Pin Assignment 1 VCC 2 In 3 GND 4 Out IP67 Ø = 54 mm Ø = 10 mm Order number: 002	Pin Assignment 1 VCC 2 In 3 GND 4 Out IP67, IP69K Ø = 65 mm Ø = 10 mm Order number: 004	Pin Assignment 1 Out 2 GND 3 VCC IP67 Ø = 73 mm Ø = 10 mm Order number: 007
*without cable (order) = 00mm, with cable length = 5 mm			
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection	
Pin Assignment 1 GND 2 VCC 3 VCC 4 Out IP67 Ø = 38 mm Ø = 10 mm Order number: 008	Pin Assignment A VCC B GND C Out IP67 Ø = 38 mm Ø = 10 mm Order number: 009	Color Assignment Red VCC White Out Black GND IP67 Ø = 64 mm Ø = 20 mm Order number: 011	
Thread code: 01	Thread code: 02	Thread code: 03	Thread code: 04
Thread code: 05	Thread code: 06	Thread code: 07	Thread code: 08