



SUCO 0531 ELECTRONIC PRESSURE SWITCH

053125141B011

PNP output (High Side), NC, 0-25 Bar, G 1/4 – DIN EN ISO 1179-2, Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	25 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	200 bar
Pressure max	100 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS

IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale



DIN EN 175305-803-A

Pin	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}
4	U _{out}
5	U _{in}
6	U _{out}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 001

M 12 - DIN EN 4579-2-101-A

Pin	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}
4	U _{out}
5	U _{in}
6	U _{out}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 002

ISO 15170-A1-A1

Pin	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}
4	U _{out}
5	U _{in}
6	U _{out}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 003

AMP Superseal

Pin	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}
4	U _{out}
5	U _{in}
6	U _{out}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 004

DEUTSCH DT04-4P

Pin	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}
4	U _{out}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 005

DEUTSCH DT04-3P

Pin	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 006

Cable connection

Cable	Assignment
1	U _{ref}
2	U _{out}
3	U _{in}
4	U _{out}

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 007

Thread code 01

Thread code 01

Thread code 02

Thread code 02

Thread code 03

Thread code 03

Thread code 04

Thread code 04

Thread code 05

Thread code 05

Thread code 06

Thread code 06

Thread code 07

Thread code 07

Thread code 08

Thread code 08

Thread code 09

Thread code 09

Thread code 10

Thread code 10

Thread code 11

Thread code 11

Thread code 12

Thread code 12

Thread code 13

Thread code 13

Thread code 14

Thread code 14

Thread code 15

Thread code 15

Thread code 16

Thread code 16

Thread code 17

Thread code 17

Thread code 18

Thread code 18

Thread code 19

Thread code 19

Thread code 20

Thread code 20

Thread code 21

Thread code 21

Thread code 22

Thread code 22

Thread code 23

Thread code 23

Thread code 24

Thread code 24

Thread code 25

Thread code 25

Thread code 26

Thread code 26

Thread code 27

Thread code 27

Thread code 28

Thread code 28

Thread code 29

Thread code 29

Thread code 30

Thread code 30

Thread code 31

Thread code 31

Thread code 32

Thread code 32

Thread code 33

Thread code 33

Thread code 34

Thread code 34

Thread code 35

Thread code 35

Thread code 36

Thread code 36

Thread code 37

Thread code 37

Thread code 38

Thread code 38

Thread code 39

Thread code 39

Thread code 40

Thread code 40

Thread code 41

Thread code 41

Thread code 42

Thread code 42

Thread code 43

Thread code 43

Thread code 44

Thread code 44

Thread code 45

Thread code 45

Thread code 46

Thread code 46

Thread code 47

Thread code 47

Thread code 48

Thread code 48

Thread code 49

Thread code 49

Thread code 50

Thread code 50

Thread code 51

Thread code 51

Thread code 52

Thread code 52

Thread code 53

Thread code 53

Thread code 54

Thread code 54

Thread code 55

Thread code 55

Thread code 56

Thread code 56

Thread code 57

Thread code 57

Thread code 58

Thread code 58

Thread code 59

Thread code 59

Thread code 60

Thread code 60

Thread code 61

Thread code 61

Thread code 62

Thread code 62

Thread code 63

Thread code 63

Thread code 64

Thread code 64

Thread code 65

Thread code 65

Thread code 66

Thread code 66

Thread code 67

Thread code 67

Thread code 68

Thread code 68

Thread code 69

Thread code 69

Thread code 70

Thread code 70

Thread code 71

Thread code 71

Thread code 72

Thread code 72

Thread code 73

Thread code 73

Thread code 74

Thread code 74

Thread code 75

Thread code 75

Thread code 76

Thread code 76

Thread code 77

Thread code 77

Thread code 78

Thread code 78

Thread code 79

Thread code 79

Thread code 80

Thread code 80

Thread code 81

Thread code 81

Thread code 82

Thread code 82

Thread code 83

Thread code 83

Thread code 84

Thread code 84

Thread code 85

Thread code 85

Thread code 86

Thread code 86

Thread code 87

Thread code 87

Thread code 88

Thread code 88

Thread code 89

Thread code 89

Thread code 90

Thread code 90

Thread code 91

Thread code 91

Thread code 92

Thread code 92

Thread code 93

Thread code 93

Thread code 94

Thread code 94

Thread code 95

Thread code 95

Thread code 96

Thread code 96

Thread code 97

Thread code 97

Thread code 98

Thread code 98

Thread code 99

Thread code 99


Thread code 100

Thread code 100




haz 221

Connection diagrams



Do not connect directly to each connector
Vcc 2 only for 4-20 mA



Do not connect directly to each connector
Vcc 2 only for 0-5V

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DN EN 61076-2-001 A	ISO 15175-A1-4.1	AMP Superseal																																								
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Vcc</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 • 60 / 70 mm² • Ø 10 mm Order number: 001	Pin	Assignment	1	Vcc	2	Out	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Vcc</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 • 54 mm • Ø 11 mm Order number: 002	Pin	Assignment	1	Vcc	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Vcc</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 • 65 mm • Ø 11 mm Order number: 004	Pin	Assignment	1	Vcc	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>Vcc</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 • 73 mm • Ø 16 mm Order number: 007	Pin	Assignment	1	Out	2	Gnd	3	Vcc	4	Out
Pin	Assignment																																										
1	Vcc																																										
2	Out																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	Vcc																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	Vcc																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	Out																																										
2	Gnd																																										
3	Vcc																																										
4	Out																																										
* Without cable length (order 1) and cable length 1 - 10 mm																																											
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																																									
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Gnd</td></tr><tr><td>2</td><td>Vcc</td></tr><tr><td>3</td><td>V+</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 • 38 mm • Ø 11 mm Order number: 008	Pin	Assignment	1	Gnd	2	Vcc	3	V+	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>A</td><td>Vcc</td></tr><tr><td>B</td><td>Gnd</td></tr><tr><td>C</td><td>Out</td></tr></table> IP67 • 38 mm • Ø 11 mm Order number: 009	Pin	Assignment	A	Vcc	B	Gnd	C	Out	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>Vcc</td></tr><tr><td>white</td><td>Out</td></tr><tr><td>black</td><td>Gnd</td></tr></table> IP67 • 64 mm 16-20 mm band width • Ø 11 mm Order number: 011		Cable	Assignment	red	Vcc	white	Out	black	Gnd														
Pin	Assignment																																										
1	Gnd																																										
2	Vcc																																										
3	V+																																										
4	Out																																										
Pin	Assignment																																										
A	Vcc																																										
B	Gnd																																										
C	Out																																										
Cable	Assignment																																										
red	Vcc																																										
white	Out																																										
black	Gnd																																										
Thread code 01	Thread code 02	Thread code 03																																									
Thread code 04	Thread code 05	Thread code 06																																									
Thread code 07	Thread code 08	Thread code 09																																									