



SUCO 0531 ELECTRONIC PRESSURE SWITCH

053125220B011

PNP output (High Side), NC, 0-250 Bar, 7/16 – 20 UNF,
Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	250 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Function	Normally Closed (SPST)
Output	PNP
Burst pressure	2000 bar
Pressure max	1000 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS


IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






haz 221

Connection diagrams



Do not connect directly to each connector
Vcc 2 only for 0-5V



Do not connect directly to each connector
Vout 2 only for 0-5V

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DN EN 61076-3-001 A	ISO 15715-A1-4-1	AMP Superseal																																								
<table><tr><th>PIN</th><th>Assignment</th></tr><tr><td>1</td><td>Vcc</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 Order number: 000	PIN	Assignment	1	Vcc	2	Out	3	Gnd	4	Out	<table><tr><th>PIN</th><th>Assignment</th></tr><tr><td>1</td><td>Vcc</td></tr><tr><td>2</td><td>in</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 Order number: 002	PIN	Assignment	1	Vcc	2	in	3	Gnd	4	Out	<table><tr><th>PIN</th><th>Assignment</th></tr><tr><td>1</td><td>Vcc</td></tr><tr><td>2</td><td>in</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67, IP69K Order number: 004	PIN	Assignment	1	Vcc	2	in	3	Gnd	4	Out	<table><tr><th>PIN</th><th>Assignment</th></tr><tr><td>1</td><td>Out</td></tr><tr><td>2</td><td>Gnd</td></tr><tr><td>3</td><td>Vcc</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 Order number: 007	PIN	Assignment	1	Out	2	Gnd	3	Vcc	4	Out
PIN	Assignment																																										
1	Vcc																																										
2	Out																																										
3	Gnd																																										
4	Out																																										
PIN	Assignment																																										
1	Vcc																																										
2	in																																										
3	Gnd																																										
4	Out																																										
PIN	Assignment																																										
1	Vcc																																										
2	in																																										
3	Gnd																																										
4	Out																																										
PIN	Assignment																																										
1	Out																																										
2	Gnd																																										
3	Vcc																																										
4	Out																																										
*without-cable socket = 000m, with-cable socket = 1.50m																																											
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																																									
<table><tr><th>PIN</th><th>Assignment</th></tr><tr><td>1</td><td>Gnd</td></tr><tr><td>2</td><td>Vcc</td></tr><tr><td>3</td><td>Vcc</td></tr><tr><td>4</td><td>Out</td></tr></table> IP67 Order number: 008	PIN	Assignment	1	Gnd	2	Vcc	3	Vcc	4	Out	<table><tr><th>PIN</th><th>Assignment</th></tr><tr><td>A</td><td>Vcc</td></tr><tr><td>B</td><td>Gnd</td></tr><tr><td>C</td><td>Out</td></tr></table> IP67 Order number: 009	PIN	Assignment	A	Vcc	B	Gnd	C	Out	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>Vcc</td></tr><tr><td>white</td><td>Out</td></tr><tr><td>black</td><td>Gnd</td></tr></table> IP67 Order number: 011	Cable	Assignment	red	Vcc	white	Out	black	Gnd															
PIN	Assignment																																										
1	Gnd																																										
2	Vcc																																										
3	Vcc																																										
4	Out																																										
PIN	Assignment																																										
A	Vcc																																										
B	Gnd																																										
C	Out																																										
Cable	Assignment																																										
red	Vcc																																										
white	Out																																										
black	Gnd																																										
Thread code 01	Thread code 02	Thread code 03	Thread code 04																																								
Thread code 05	Thread code 06	Thread code 07	Thread code 08																																								