

SUCO 0532 ELECTRONIC PRESSURE SWITCH

053210141B011

NPN output (Low Side), NO, 0-10 Bar, G 1/4 – DIN EN

ISO 1179-2, Cable connection



- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

The SUCO 0532 electronic pressure switch is a high-performance, factory-set device featuring a compact hex-22 stainless steel housing with titanium-wetted parts and welded design, eliminating elastomer seals. It utilises advanced Silicon-on-Sapphire (SoS) sensor technology, ensuring exceptional accuracy ($\pm 0.5\%$ FS) and long-term stability ($\pm 0.1\%$ FS/year), and delivers reliable overpressure protection up to $4\times$ the rated range. Available with a single NPN (low-side) normally-open transistor output capable of handling up to 0.5 A, it supports pressure ranges from 0–10 bar up to 0–600 bar. The 0532 offers a wide choice of process ports and electrical connections, and includes factory-set switching point and hysteresis, along with a fast response time of under 4 ms.

The 0532 is ideal for high-integrity industrial and mobile hydraulic applications, such as in construction equipment, off-road vehicles, and pneumatic systems, where compactness, precision, and reliability are crucial. Its robust SoS sensor and welded housing offer high resilience to vibration, transient pressures, and wash-down conditions, making it suitable for severe environmental exposure. The NPN output with normally open configuration and field-programmed hysteresis allows seamless integration into PLC and relay-controlled systems for safety interlocks, pressure monitoring, and automated shutdown scenarios. The switch's fast response and low moving-part design reduce wear and improve lifespan, making the SUCO 0532 a dependable solution in OEM systems requiring compact, rugged, and high-precision pressure switching.

TECHNICAL DATA

GENERAL DATA

Adjustment range max	10 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally open
Output	NPN
Burst pressure	80 bar
Pressure max	40 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS


IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






hex 22

Connection diagrams



For component depending on each connection
*NOT any for GND



For component depending on each connection
*NOT any for GND

Technical modifications and errors excepted.

DIN EN 15120-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15175-A1-4.1	AMP Superseal																																								
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	Out	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out
Pin	Assignment																																										
1	In																																										
2	Out																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
IP67	IP67	IP67	IP67																																								
• 60 / 75 mm ² • Ø 10 mm Order number: 001	• 54 mm • Ø 11 mm Order number: 002	• 65 mm (max) • Ø 11 mm Order number: 004	• 73 mm • Ø 16 mm Order number: 003																																								
* without copper braid (+) = 0 mm, with copper braid (+) = 75 mm																																											
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																																									
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Gnd</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>In</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	Gnd	2	In	3	In	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>		Cable	Assignment	1	In	2	In	3	Gnd	4	Out												
Pin	Assignment																																										
1	Gnd																																										
2	In																																										
3	In																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
Cable	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
IP67	IP67	IP67																																									
• 38 mm • Ø 21 mm Order number: 004	• 38 mm • Ø 21 mm Order number: 005	• 64 mm Ø 20 mm (cable length = 2 m) • Ø 22 mm Order number: 011																																									
Thread code: 01	Thread code: 03	Thread code: 04	Thread code: 09																																								
Thread code: 10	Thread code: 12	Thread code: 21	Thread code: 42																																								

DIN EN 15120-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15175-A1-4.1	AMP Superseal																																								
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	Out	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out
Pin	Assignment																																										
1	In																																										
2	Out																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
IP67	IP67	IP67	IP67																																								
• 60 / 75 mm ² • Ø 10 mm Order number: 001	• 54 mm • Ø 11 mm Order number: 002	• 65 mm (max) • Ø 11 mm Order number: 004	• 73 mm • Ø 16 mm Order number: 003																																								
* without copper cable = Ø 10 mm, with copper cable = 15 mm																																											
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																																									
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Gnd</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>In</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	Gnd	2	In	3	In	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>red</td><td>In</td></tr><tr><td>blue</td><td>In</td></tr><tr><td>black</td><td>Gnd</td></tr></table>		Cable	Assignment	red	In	blue	In	black	Gnd														
Pin	Assignment																																										
1	Gnd																																										
2	In																																										
3	In																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
Cable	Assignment																																										
red	In																																										
blue	In																																										
black	Gnd																																										
IP67	IP67	IP67																																									
• 38 mm • Ø 21 mm Order number: 004	• 38 mm • Ø 21 mm Order number: 005	• 64 mm Ø 20 mm (cable length = 2 m) • Ø 22 mm Order number: 011																																									
Thread code: 01	Thread code: 03	Thread code: 04	Thread code: 09																																								
Thread code: 10	Thread code: 12	Thread code: 21	Thread code: 42																																								