



SUCO 0532 ELECTRONIC PRESSURE SWITCH

053225103B011
NPN output (Low Side), NO, 0-25 Bar, G 1/4 – DIN
3852-A, Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	25 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally open (SPST)
Output	NPN
Burst pressure	200 bar
Pressure max	100 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g


IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






haz 221

Connection diagrams



Do not connect directly to each connector
Vcc 2 only for 0-5V



Do not connect directly to each connector
Vcc 2 only for 0-5V

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DN EN 61076-2-001 A	ISO 15175-A1-4.1	AMP Superseal
Pin Assignment 1 Vcc 2 Out 3 Gnd 4 Out IP67	Pin Assignment 1 Vcc 2 In 3 Gnd 4 Out IP67	Pin Assignment 1 Vcc 2 In 3 Gnd 4 Out IP67	Pin Assignment 1 Out 2 Gnd 3 Vcc 4 In IP67
IP67 • 60 / 70 mm ² • Ø 10 mm Order number: 000	IP67 • 54 mm • Ø 11 mm Order number: 002	IP67, IP69K • 65 mm • Ø 11 mm Order number: 004	IP67 • 71 mm • Ø 16 mm Order number: 007
*without cable (code 1) = 00mm, with cable (code 1) = 2mm			
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection	
Pin Assignment 1 Gnd 2 Vcc 3 V+ 4 Out IP67	Pin Assignment A Vcc B Gnd C Out IP67	Cable Assignment red Vcc white Out black Gnd IP67	
• 38 mm • Ø 11 mm Order number: 008	• 38 mm • Ø 11 mm Order number: 009	IP67 • 64 mm 10-20 mm band adjust cable length = 2 m • Ø 11 mm Order number: 011	
Thread code: 01	Thread code: 02	Thread code: 03	Thread code: 04
Thread code: 05	Thread code: 06	Thread code: 07	Thread code: 08