



SUCO 0532 ELECTRONIC PRESSURE SWITCH

053225109B008
NPN output (Low Side), NO, 0-25 Bar, NPT 1/4,
Deutsch DT04-4P

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	25 bar
Adjustment range min	0 bar
Electrical connection	Deutsch DT04-4P
Process connection	1/4 NPT
Function	Normally open (SPST)
Output	NPN
Burst pressure	200 bar
Pressure max	100 bar

TEMPERATURE & MATERIALS DATA

Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium





ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	80 g

SAFETY & APPROVALS

IP class	IP67, IP6K9K
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s ² ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale




DIN EN 175301-803-A	M 12 - DIN EN 61076-2-103-A	ISO 15170-A1-K1	AMP Superseal																																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 60/7/16 mm³ • D 30 mm Order number: 001 <small>* without cable length = 0.0m, with cable length = 1.5m</small></p>	1	Out	2	Out	3	Out	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 22 mm Order number: 002 <small>* without cable length = 0.0m, with cable length = 1.5m</small></p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 22 mm Order number: 004</p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 71 mm • D 28 mm Order number: 007</p>	1	Out	2	Out	3	Out	4	Out
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								

DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 008</p>	1	Out	2	Out	3	NC	4	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 010</p>	1	Line	2	Out	3	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>white</td></tr> <tr><td>3</td><td>black</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 68 mm (a 20 mm hand held cable length = 7 m) • D 22 mm Order number: 011</p>	1	Line	2	white	3	black	4	Out
1	Out																							
2	Out																							
3	NC																							
4	Out																							
1	Line																							
2	Out																							
3	Out																							
1	Line																							
2	white																							
3	black																							
4	Out																							


Thread code 01	Thread code 02	Thread code 03	Thread code 04
 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 008</p>	 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 010</p>	 <p>IP67</p> <p>• 68 mm (a 20 mm hand held cable length = 7 m) • D 22 mm Order number: 011</p>	 <p>IP67</p> <p>• 71 mm • D 28 mm Order number: 007</p>
Thread code 05	Thread code 06	Thread code 07	Thread code 08
 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 008</p>	 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 010</p>	 <p>IP67</p> <p>• 68 mm (a 20 mm hand held cable length = 7 m) • D 22 mm Order number: 011</p>	 <p>IP67</p> <p>• 71 mm • D 28 mm Order number: 007</p>



hex 21







No pinout opening in each connector 10/20 key for 001



No pinout opening in each connector 10/20 key for 001

Technical modifications and errors excepted.

DIN EN 175301-803-A	M 12 - DIN EN 61076-2-103-A	ISO 15170-A1-K1	AMP Superseal																																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 60/7/16 mm³ • D 30 mm Order number: 001 <small>* without cable length = 0.0m, with cable length = 1.5m</small></p>	1	Out	2	Out	3	Out	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 22 mm Order number: 002 <small>* without cable length = 0.0m, with cable length = 1.5m</small></p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>NC</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> <tr><td>5</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 54 mm • D 22 mm Order number: 004</p>	1	Line	2	NC	3	NC	4	Out	5	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 71 mm • D 28 mm Order number: 007</p>	1	Out	2	Out	3	Out	4	Out
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Line																																								
2	NC																																								
3	NC																																								
4	Out																																								
5	Out																																								
1	Out																																								
2	Out																																								
3	Out																																								
4	Out																																								

DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																						
 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Out</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>NC</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 008</p>	1	Out	2	Out	3	NC	4	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>Out</td></tr> <tr><td>3</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 010</p>	1	Line	2	Out	3	Out	 <p>Pin Assignment</p> <table border="1"> <tr><td>1</td><td>Line</td></tr> <tr><td>2</td><td>white</td></tr> <tr><td>3</td><td>black</td></tr> <tr><td>4</td><td>Out</td></tr> </table> <p>IP67</p> <p>• 68 mm (a 20 mm hand held cable length = 7 m) • D 22 mm Order number: 011</p>	1	Line	2	white	3	black	4	Out
1	Out																							
2	Out																							
3	NC																							
4	Out																							
1	Line																							
2	Out																							
3	Out																							
1	Line																							
2	white																							
3	black																							
4	Out																							

Thread code 01	Thread code 02	Thread code 03	Thread code 04
 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 008</p>	 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 010</p>	 <p>IP67</p> <p>• 68 mm (a 20 mm hand held cable length = 7 m) • D 22 mm Order number: 011</p>	 <p>IP67</p> <p>• 71 mm • D 28 mm Order number: 007</p>
Thread code 05	Thread code 06	Thread code 07	Thread code 08
 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 008</p>	 <p>IP67</p> <p>• 38 mm • D 22 mm Order number: 010</p>	 <p>IP67</p> <p>• 68 mm (a 20 mm hand held cable length = 7 m) • D 22 mm Order number: 011</p>	 <p>IP67</p> <p>• 71 mm • D 28 mm Order number: 007</p>