

SUCO 0532 ELECTRONIC PRESSURE SWITCH

053225241B011

NPN output (Low Side), NO, 0-250 Bar, G 1/4 – DIN EN
ISO 1179-2, Cable connection



- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

The SUCO 0532 electronic pressure switch is a high-performance, factory-set device featuring a compact hex-22 stainless steel housing with titanium-wetted parts and welded design, eliminating elastomer seals. It utilises advanced Silicon-on-Sapphire (SoS) sensor technology, ensuring exceptional accuracy ($\pm 0.5\%$ FS) and long-term stability ($\pm 0.1\%$ FS/year), and delivers reliable overpressure protection up to $4\times$ the rated range. Available with a single NPN (low-side) normally-open transistor output capable of handling up to 0.5 A, it supports pressure ranges from 0–10 bar up to 0–600 bar. The 0532 offers a wide choice of process ports and electrical connections, and includes factory-set switching point and hysteresis, along with a fast response time of under 4 ms.

The 0532 is ideal for high-integrity industrial and mobile hydraulic applications, such as in construction equipment, off-road vehicles, and pneumatic systems, where compactness, precision, and reliability are crucial. Its robust SoS sensor and welded housing offer high resilience to vibration, transient pressures, and wash-down conditions, making it suitable for severe environmental exposure. The NPN output with normally open configuration and field-programmed hysteresis allows seamless integration into PLC and relay-controlled systems for safety interlocks, pressure monitoring, and automated shutdown scenarios. The switch's fast response and low moving-part design reduce wear and improve lifespan, making the SUCO 0532 a dependable solution in OEM systems requiring compact, rugged, and high-precision pressure switching.

TECHNICAL DATA

GENERAL DATA

Adjustment range max	250 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally open
Output	NPN
Burst pressure	2000 bar
Pressure max	1000 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS


IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






hex 22

Connection diagrams



For component operating in each connection
*H072 only for 05A



For component operating in each connection
*H072 only for 05A

Technical modifications and errors excepted.

DIN EN 15120-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15175-A1-4.1	AMP Superseal																																								
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>Out</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	Out	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	4	Out
Pin	Assignment																																										
1	In																																										
2	Out																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
4	Out																																										
IP67	IP67	IP67	IP67																																								
• 60 / 75 mm ²	• 54 mm	• 65 mm (max)	• 73 mm																																								
• Ø 10 mm	• Ø 10 mm	• Ø 10 mm	• Ø 10 mm																																								
Order number: 001	Order number: 002	Order number: 004	Order number: 003																																								
* without copper braid (+) = 0 mm, with copper braid (+) = 75 mm																																											
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection																																									
<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>Gnd</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>In</td></tr><tr><td>4</td><td>Out</td></tr></table>	Pin	Assignment	1	Gnd	2	In	3	In	4	Out	<table><tr><th>Pin</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>3</td><td>Gnd</td></tr></table>	Pin	Assignment	1	In	2	In	3	Gnd	<table><tr><th>Cable</th><th>Assignment</th></tr><tr><td>1</td><td>In</td></tr><tr><td>2</td><td>In</td></tr><tr><td>white</td><td>Gnd</td></tr><tr><td>3</td><td>Out</td></tr></table>	Cable	Assignment	1	In	2	In	white	Gnd	3	Out													
Pin	Assignment																																										
1	Gnd																																										
2	In																																										
3	In																																										
4	Out																																										
Pin	Assignment																																										
1	In																																										
2	In																																										
3	Gnd																																										
Cable	Assignment																																										
1	In																																										
2	In																																										
white	Gnd																																										
3	Out																																										
IP67	IP67	IP67																																									
• 38 mm	• 38 mm	• 64 mm (max)																																									
• Ø 21 mm	• Ø 21 mm	• Ø 21 mm (max)																																									
Order number: 004	Order number: 005	Order number: 011																																									
1/8 inch NPT	1/4 inch NPT	3/8 inch NPT	1/2 inch NPT																																								
Thread code: 01	Thread code: 03	Thread code: 04	Thread code: 09																																								
1/2 inch NPT	3/4 inch NPT	1 inch NPT	1 1/2 inch NPT																																								
Thread code: 10	Thread code: 12	Thread code: 14	Thread code: 16																																								

DIN EN 15120-803-A	M 12 - DIN EN 61076-2-101 A	ISO 15175-A1-4.1	AMP Superseal
Pin: Assigned 1 In 2 Out 3 Gnd 4 Out	Pin: Assigned 1 In 2 In 3 Gnd 4 Out	Pin: Assigned 1 In 2 In 3 Gnd 4 Out	Pin: Assigned 1 In 2 In 3 Gnd 4 Out
IP67 • 60 / 75 mm ² • Ø 10 mm Order number: 001	IP67 • 54 mm • Ø 10 mm Order number: 002	IP67 • 65 mm (max) • Ø 10 mm Order number: 004	IP67 • 73 mm • Ø 10 mm Order number: 003
* without copper cable = 010m, with copper cable = 15 mm			
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection	
Pin: Assigned 1 Gnd 2 In 3 In 4 Out	Pin: Assigned 1 In 2 In 3 Gnd	Cable: Assigned red In white In black Gnd green Out	
IP67 • 38 mm • Ø 21 mm Order number: 004	IP67 • 38 mm • Ø 21 mm Order number: 005	IP67 • 64 mm (max) (20 mm bend shell) • Cable length: 2 m • Ø 21 mm Order number: 011	
Thread code: 01 1/8 inch NPT Order number: 004	Thread code: 03 1/4 inch NPT Order number: 005	Thread code: 04 3/8 inch NPT Order number: 011	Thread code: 09 1/2 inch NPT Order number: 009
Thread code: 10 1/2 inch NPT Order number: 010	Thread code: 12 3/4 inch NPT Order number: 012	Thread code: 14 1 inch NPT Order number: 014	Thread code: 16 1 1/2 inch NPT Order number: 016