



SUCO 0532 ELECTRONIC PRESSURE SWITCH

053260242B011

NPN output (Low Side), NO, 0-600 Bar, M14x1.5 – DIN
EN ISO 9974-2, Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	600 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	M14x1.5
Function	Normally open (SPST)
Output	NPN
Burst pressure	2000 bar
Pressure max	1650 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS


IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale






haz 221

Connection diagrams



Do not connect directly to each connector
NUT only for 0630



Do not connect directly to each connector
NUT only for 0630

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DIN EN 61076-3-001 A	ISO 15715-A1-4-1	AMP Superseal
Pin Assignment 1 Vcc 2 Out 3 Gnd 4 Out IP67 • 60 / 70 mm² • Ø 10 mm Order number: 001 * without copper socket = 70 mm	Pin Assignment 1 Vcc 2 Out 3 Gnd 4 Out IP67 • 54 mm • Ø 11 mm Order number: 002	Pin Assignment 1 Vcc 2 Out 3 Gnd 4 Out IP67 • 65 mm • Ø 11 mm Order number: 004	Pin Assignment 1 Vcc 2 Out 3 Gnd 4 Out IP67 • 71 mm • Ø 16 mm Order number: 007
* without copper socket = 70 mm			
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection	
Pin Assignment 1 Gnd 2 Vcc 3 Vcc 4 Out IP67 • 38 mm • Ø 11 mm Order number: 008	Pin Assignment A Vcc B Gnd C Out IP67 • 38 mm • Ø 11 mm Order number: 009	Color Assignment Red Vcc White Out Black Gnd IP67 • 64 mm • 20 mm band width • Cable length = 2 m • Ø 11 mm Order number: 011	
Thread code: 01	Thread code: 02	Thread code: 03	Thread code: 04
Thread code: 05	Thread code: 06	Thread code: 07	Thread code: 08
Thread code: 09	Thread code: 10	Thread code: 21	Thread code: 09