



## SUCO 0533 ELECTRONIC PRESSURE SWITCH

053310141B004

NPN output (Low Side), NC, 0-10 Bar, G 1/4 – DIN EN ISO 1179-2, Bayonet ISO 15170-A1-4.1

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



### PRODUCT DESCRIPTION

### TECHNICAL DATA

#### GENERAL DATA

|                      |                        |
|----------------------|------------------------|
| Adjustment range max | 10 bar                 |
| Adjustment range min | 0 bar                  |
| Process connection   | G1/4                   |
| Function             | Normally Closed (SPST) |
| Output               | NPN                    |
| Burst pressure       | 80 bar                 |
| Pressure max         | 40 bar                 |

#### TEMPERATURE & MATERIALS DATA


|                           |                                  |
|---------------------------|----------------------------------|
| Temperature of media from | -40 °C                           |
| Temperature of media to   | 125 °C                           |
| Temperature ambient from  | -40 °C                           |
| Temperature ambient to    | 100 °C                           |
| Material of body          | Stainless steel 1.4305           |
| Material of wetted parts  | Stainless steel 1.4305, Titanium |

### ADDITIONAL DATA

|                                  |                                                                                    |
|----------------------------------|------------------------------------------------------------------------------------|
| Supply voltage dc max            | 32 V DC                                                                            |
| Supply voltage dc min            | 9.6 V DC                                                                           |
| Pressure rise                    | ≤ 5,000 bar/s                                                                      |
| Switching time                   | < 2 ms                                                                             |
| Switching point adjustment range | 2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory |
| Weight                           | 80 g                                                                               |


### SAFETY & APPROVALS

|                            |                                                                           |
|----------------------------|---------------------------------------------------------------------------|
| IP class                   | IP67, IP6K9K                                                              |
| Hysteresis                 | 2..99.8% of nominal pressure range (full scale), programmable at factory  |
| Shock resistance           | 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27                        |
| Vibration resistance       | 20g: 4..2000 Hz sine wave, DIN EN 60068-2-6                               |
| EMC                        | EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007                      |
| Accuracy                   | ±0.5 % of adjustment range (Full scale) at room temperature               |
| Long term stability        | ±0.1 % of adjustment range (full scale) per year                          |
| Mechanical life expectancy | 10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure |
| Repeatability              | ±0.1 % full scale                                                         |




Item 221

Connection diagrams



Pin assignment depending on each connection  
"NPN" only for 254x



Pin assignment depending on each connection  
"NPN" only for 254x

Technical modifications and errors excepted.

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | Out        |
| 3   | Out        |
| 4   | Out        |

IP67  
 L = 60/75 mm  
 Ø = Ø 30 mm  
 Order number: 001

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | NC         |
| 3   | NC         |
| 4   | Out        |

IP67  
 L = 54 mm  
 Ø = Ø 22 mm  
 Order number: 002

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | NC         |
| 3   | NC         |
| 4   | Out        |

IP67  
 L = 65 mm  
 Ø = Ø 27 mm  
 Order number: 004

| Pin | Assignment |
|-----|------------|
| 1   | Out        |
| 2   | Out        |
| 3   | Line       |

IP67  
 L = 71 mm  
 Ø = Ø 28 mm  
 Order number: 007

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | Line       |
| 3   | NC         |
| 4   | Out        |

IP67  
 L = 58 mm  
 Ø = Ø 22 mm  
 Order number: 008

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | Line       |
| 3   | Out        |

IP67  
 L = 58 mm  
 Ø = Ø 22 mm  
 Order number: 010

Cable connection

| Cable | Assignment |
|-------|------------|
| red   | Line       |
| white | Out        |
| black | Out        |

IP67  
 L = 68 mm  
 (ø 20 mm band adjust)  
 cable length = 2 m  
 Ø = Ø 22 mm  
 Order number: 011

Thread code: 41

Thread code: 03

Thread code: 04

Thread code: 09

Thread code: 05

Thread code: 20

Thread code: 21

Thread code: 42

hex 22  
 Connection diagrams  
 No. assigned opening in each connector  
 1/22 key for 004  
 1/22 key for 009  
 1/22 key for 011  
 1/22 key for 012  
 1/22 key for 013  
 1/22 key for 014  
 1/22 key for 015  
 1/22 key for 016  
 1/22 key for 017  
 1/22 key for 018  
 1/22 key for 019  
 1/22 key for 020  
 1/22 key for 021  
 1/22 key for 022  
 1/22 key for 023  
 1/22 key for 024  
 1/22 key for 025  
 1/22 key for 026  
 1/22 key for 027  
 1/22 key for 028  
 1/22 key for 029  
 1/22 key for 030  
 1/22 key for 031  
 1/22 key for 032  
 1/22 key for 033  
 1/22 key for 034  
 1/22 key for 035  
 1/22 key for 036  
 1/22 key for 037  
 1/22 key for 038  
 1/22 key for 039  
 1/22 key for 040  
 1/22 key for 041  
 1/22 key for 042  
 1/22 key for 043  
 1/22 key for 044  
 1/22 key for 045  
 1/22 key for 046  
 1/22 key for 047  
 1/22 key for 048  
 1/22 key for 049  
 1/22 key for 050  
 1/22 key for 051  
 1/22 key for 052  
 1/22 key for 053  
 1/22 key for 054  
 1/22 key for 055  
 1/22 key for 056  
 1/22 key for 057  
 1/22 key for 058  
 1/22 key for 059  
 1/22 key for 060  
 1/22 key for 061  
 1/22 key for 062  
 1/22 key for 063  
 1/22 key for 064  
 1/22 key for 065  
 1/22 key for 066  
 1/22 key for 067  
 1/22 key for 068  
 1/22 key for 069  
 1/22 key for 070  
 1/22 key for 071  
 1/22 key for 072  
 1/22 key for 073  
 1/22 key for 074  
 1/22 key for 075  
 1/22 key for 076  
 1/22 key for 077  
 1/22 key for 078  
 1/22 key for 079  
 1/22 key for 080  
 1/22 key for 081  
 1/22 key for 082  
 1/22 key for 083  
 1/22 key for 084  
 1/22 key for 085  
 1/22 key for 086  
 1/22 key for 087  
 1/22 key for 088  
 1/22 key for 089  
 1/22 key for 090  
 1/22 key for 091  
 1/22 key for 092  
 1/22 key for 093  
 1/22 key for 094  
 1/22 key for 095  
 1/22 key for 096  
 1/22 key for 097  
 1/22 key for 098  
 1/22 key for 099  
 1/22 key for 100

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | Out        |
| 3   | Out        |
| 4   | Out        |

IP67  
 L = 60/75 mm  
 Ø = Ø 30 mm  
 Order number: 001

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | NC         |
| 3   | NC         |
| 4   | Out        |

IP67  
 L = 54 mm  
 Ø = Ø 22 mm  
 Order number: 002

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | NC         |
| 3   | NC         |
| 4   | Out        |

IP67  
 L = 65 mm  
 Ø = Ø 27 mm  
 Order number: 004

| Pin | Assignment |
|-----|------------|
| 1   | Out        |
| 2   | Out        |
| 3   | Line       |

IP67  
 L = 71 mm  
 Ø = Ø 28 mm  
 Order number: 007

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | Line       |
| 3   | NC         |
| 4   | Out        |

IP67  
 L = 58 mm  
 Ø = Ø 22 mm  
 Order number: 008

| Pin | Assignment |
|-----|------------|
| 1   | Line       |
| 2   | Line       |
| 3   | Out        |

IP67  
 L = 58 mm  
 Ø = Ø 22 mm  
 Order number: 010

Cable connection

| Cable | Assignment |
|-------|------------|
| red   | Line       |
| white | Out        |
| black | Out        |

IP67  
 L = 68 mm  
 (ø 20 mm band adjust)  
 cable length = 2 m  
 Ø = Ø 22 mm  
 Order number: 011

Thread code: 41

Thread code: 03

Thread code: 04

Thread code: 09

Thread code: 05

Thread code: 20

Thread code: 21

Thread code: 42