



SUCO 0533 ELECTRONIC PRESSURE SWITCH

053360241B011

NPN output (Low Side), NC, 0-600 Bar, G 1/4 – DIN EN ISO 1179-2, Cable connection

- One Switching Output
- Stainless Steel & Titanium Wetted Parts
- Silicon-On-Sapphire Technology
- Factory Set



PRODUCT DESCRIPTION

TECHNICAL DATA

GENERAL DATA

Adjustment range max	600 bar
Adjustment range min	0 bar
Electrical connection	Embedded 2m cable
Process connection	G1/4
Function	Normally Closed (SPST)
Output	NPN
Burst pressure	2000 bar
Pressure max	1650 bar

TEMPERATURE & MATERIALS DATA


Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range Full Scale (FS), programmable at factory
Weight	135 g

SAFETY & APPROVALS

IP class	IP67
Hysteresis	2..99.8% of nominal pressure range (full scale), programmable at factory
Shock resistance	500m / s²; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g; 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of adjustment range (Full scale) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale



DIN EN 175305-803-A

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 001

M 12 - DIN EN 4579-2-101-A

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 002

ISO 15170-A1-A1

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 003

AMP Superseal

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 004

DEUTSCH DT04-4P

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl
4	Out

PS

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 005

DEUTSCH DT04-3P

Pin	Assignment
1	Ctrl
2	Out
3	Ctrl

PS

IP67

• 10 x 10 mm

• 10 x 10 mm

Order number: 006

Cable connection

• 10 x 10 mm

• 10 x 10 mm

Order number: 007

Thread code: 01

Thread code: 01

Thread code: 02

Thread code: 02

Thread code: 03

Thread code: 03

Thread code: 04

Thread code: 04

Thread code: 05

Thread code: 05

Thread code: 06

Thread code: 06

Thread code: 07

Thread code: 07

Thread code: 08

Thread code: 08

Thread code: 09

Thread code: 09

Thread code: 10

Thread code: 10

Thread code: 11

Thread code: 11

Thread code: 12

Thread code: 12

Thread code: 13

Thread code: 13

Thread code: 14

Thread code: 14

Thread code: 15

Thread code: 15

Thread code: 16

Thread code: 16

Thread code: 17

Thread code: 17

Thread code: 18

Thread code: 18

Thread code: 19

Thread code: 19

Thread code: 20

Thread code: 20

Thread code: 21

Thread code: 21

Thread code: 22

Thread code: 22

Thread code: 23

Thread code: 23

Thread code: 24

Thread code: 24

Thread code: 25

Thread code: 25

Thread code: 26

Thread code: 26

Thread code: 27

Thread code: 27

Thread code: 28

Thread code: 28

Thread code: 29

Thread code: 29

Thread code: 30

Thread code: 30

Thread code: 31

Thread code: 31

Thread code: 32

Thread code: 32

Thread code: 33

Thread code: 33

Thread code: 34

Thread code: 34

Thread code: 35

Thread code: 35

Thread code: 36

Thread code: 36

Thread code: 37

Thread code: 37

Thread code: 38

Thread code: 38

Thread code: 39

Thread code: 39

Thread code: 40

Thread code: 40

Thread code: 41

Thread code: 41

Thread code: 42

Thread code: 42

Thread code: 43

Thread code: 43

Thread code: 44

Thread code: 44

Thread code: 45

Thread code: 45

Thread code: 46

Thread code: 46

Thread code: 47

Thread code: 47

Thread code: 48

Thread code: 48

Thread code: 49

Thread code: 49

Thread code: 50

Thread code: 50

Thread code: 51

Thread code: 51

Thread code: 52

Thread code: 52

Thread code: 53

Thread code: 53

Thread code: 54

Thread code: 54

Thread code: 55

Thread code: 55

Thread code: 56

Thread code: 56

Thread code: 57

Thread code: 57

Thread code: 58

Thread code: 58

Thread code: 59

Thread code: 59

Thread code: 60

Thread code: 60

Thread code: 61

Thread code: 61

Thread code: 62

Thread code: 62

Thread code: 63

Thread code: 63

Thread code: 64

Thread code: 64

Thread code: 65

Thread code: 65

Thread code: 66

Thread code: 66

Thread code: 67

Thread code: 67

Thread code: 68

Thread code: 68

Thread code: 69

Thread code: 69

Thread code: 70

Thread code: 70

Thread code: 71

Thread code: 71

Thread code: 72

Thread code: 72

Thread code: 73

Thread code: 73

Thread code: 74

Thread code: 74

Thread code: 75

Thread code: 75

Thread code: 76

Thread code: 76

Thread code: 77

Thread code: 77

Thread code: 78

Thread code: 78

Thread code: 79

Thread code: 79

Thread code: 80

Thread code: 80

Thread code: 81

Thread code: 81

Thread code: 82

Thread code: 82

Thread code: 83

Thread code: 83

Thread code: 84

Thread code: 84

Thread code: 85

Thread code: 85

Thread code: 86

Thread code: 86

Thread code: 87

Thread code: 87

Thread code: 88

Thread code: 88

Thread code: 89

Thread code: 89

Thread code: 90

Thread code: 90

Thread code: 91

Thread code: 91

Thread code: 92

Thread code: 92

Thread code: 93

Thread code: 93

Thread code: 94

Thread code: 94

Thread code: 95

Thread code: 95

Thread code: 96

Thread code: 96

Thread code: 97

Thread code: 97

Thread code: 98

Thread code: 98

Thread code: 99

Thread code: 99


Thread code: 100

Thread code: 100




haz 221

Connection diagrams



Do not connect directly to each connector
Vcc 2 only for 0-5V



Do not connect directly to each connector
Vcc 2 only for 0-5V

Technical modifications and errors excepted.

DN EN 175301-803-A	M 12 - DN EN 61076-2-001 A	ISO 15715-A1-4-1	AMP Superseal
Pin Assignment 1 Vcc 2 Out 3 Gnd 4 Out	Pin Assignment 1 Vcc 2 In 3 Gnd 4 Out	Pin Assignment 1 Vcc 2 In 3 Gnd 4 Out	Pin Assignment 1 Out 2 Gnd 3 Vcc 4 In
IP67 • 60 / 70 mm² • Ø 10 mm	IP67 • 54 mm • Ø 11 mm	IP67 • 65 mm • Ø 11 mm	IP67 • 71 mm • Ø 16 mm
Order number: 001	Order number: 002	Order number: 004	Order number: 007
* without copper shield 4P - 15 mm			
DEUTSCH DT04-4P	DEUTSCH DT04-3P	Cable connection	
Pin Assignment 1 Gnd 2 Vcc 3 Vcc 4 Out	Pin Assignment A Vcc B Gnd C Out	Color Assignment Red Vcc White Out Black Gnd	
IP67 • 38 mm • Ø 11 mm	IP67 • 38 mm • Ø 11 mm	IP67 • 64 mm • 20 mm band width • Cable length = 2 m • Ø 11 mm	
Order number: 008	Order number: 009	Order number: 011	
Thread code: 01	Thread code: 02	Thread code: 03	Thread code: 04
Thread code: 05	Thread code: 06	Thread code: 07	Thread code: 08