**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# SUCO 0540 ELECTRONIC PRESSURE SWITCH

054010242B011
PNP output (High Side), NO / NO, 0-100 Bar, M14x1.5 – DIN EN ISO 9974-2, Cable connection




- Up to four times in overpressure protection
- Durable and long lasting even in high pressure environments
- Functional in a wide range of temperatures
- Ideal for mobile hydraulic applications

### PRODUCT DESCRIPTION

The SUCO 0540 is a compact, rugged electronic pressure switch based on Silicon-on-Sapphire (SoS) technology, offering exceptional accuracy, reliability, and long-term stability. It features a stainless steel AISI 303 and titanium wetted construction, ensuring compatibility with a wide range of hydraulic and pneumatic media and high overpressure protection. The switch supports dual PNP (high side) transistor outputs in a normally open (NO/NO) configuration, capable of handling currents up to 500 mA, with built-in short-circuit, overvoltage, and reverse polarity protection. With nominal pressure ranges from low vacuum up to 1,650 bar, factory-set switching point and hysteresis (adjustable from 0.2 to 99.8 % FS), temperature compensation, and long-term stability, it's designed for demanding applications. Voltage supply is wide (9.6–32 VDC), with low idle power (< 15 mA), and a choice of electrical connectors (AMP Superseal, Deutsch, DIN, M12, cable) and process thread types ensures flexible installation options.
The 0540 is ideal for harsh mobile-hydraulic environments, construction machinery, off-road vehicles, agricultural systems, where ruggedness and reliable switching under dynamic pressure conditions matter most. It also fits industrial pneumatic and hydraulic systems requiring precise pressure monitoring and control with electrical interfaces. Its overpressure resilience and durable welded stainless housing make it suitable for OEM safety interlock systems, high-pressure test rigs, and medical-gas installations rated to IP67/IP6K9K, standing up to wash-down, shock, and vibration. Furthermore, the dual-switch outputs enable simple integration into PLC logic or relay circuits for event-driven control (e.g. pressure alerts, automated shutdowns), especially in embedded system designs where compact size and factory-set reliability are priorities.

# TECHNICAL DATA

## GENERAL DATA

| | |
|---|---|
| **Adjustment range max** | 100 bar |
| **Adjustment range min** | 0 bar |
| **Electrical connection** | Embedded 2m cable |
| **Process connection** | M14x1.5 |
| **Function** | 2 x N/O |
| **Output** | 2 x PNP |
| **Burst pressure** | 800 bar |
| **Pressure max** | 400 bar |

## TEMPERATURE & MATERIALS DATA

| | |
|---|---|
| **Temperature of media from** | -40 °C |
| **Temperature of media to** | 125 °C |
| **Temperature ambient from** | -40 °C |
| **Temperature ambient to** | 100 °C |
| **Material of body** | Stainless steel 1.4305 |
| **Material of wetted parts** | Stainless steel 1.4305, Titanium |

## ADDITIONAL DATA

| | |
|---|---|
| **Supply voltage dc max** | 32 V DC |
| **Supply voltage dc min** | 9.6 V DC |
| **Pressure rise** | ≤ 5,000 bar/s |
| **Switching time** | < 2 ms |
| **Switching point adjustment range** | 2 … 100 % of the nominal pressure range (Full Scale, FS), programmable at factory |
| **Weight** | 135 g |

## SAFETY & APPROVALS

| | |
|---|---|
| **IP class** | IP67 |
| **Hysteresis** | 0.2…99.8 % of the nominal pressure range (Full Scale), programmable at factory |
| **Shock resistance** | 500m / s²; 11 ms half sine wave; DIN EN 60068-2-27 |
| **Vibration resistance** | 20g: 4..2000 Hz sine wave, DIN EN 60068-2-6 |
| **EMC** | EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007 |
| **Accuracy** | ±0.5 % of the nominal pressure range (FS) at room temperature |
| **Long term stability** | ±0.1 % of adjustment range (full scale) per year |
| **Mechanical life expectancy** | 10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure |
| **Repeatability** | ±0.1 % full scale |

