

**SUCO 0542 ELECTRONIC PRESSURE SWITCH**054260203B002  
PNP output (High Side), NO / NC, 0-600 Bar, G 1/4 –  
DIN 3852-A, M12 - DIN EN 61076-2-101-A**PRODUCT DESCRIPTION****TECHNICAL DATA****GENERAL DATA**

Adjustment range max	600 bar
Adjustment range min	0 bar
Electrical connection	M12x1
Process connection	G1/4
Function	1 x N/O & 1 x N/C
Output	2 x PNP
Burst pressure	2000 bar
Pressure max	1650 bar

**TEMPERATURE & MATERIALS DATA**

Temperature of media from	-40 °C
Temperature of media to	125 °C
Temperature ambient from	-40 °C
Temperature ambient to	100 °C
Material of body	Stainless steel 1.4305
Material of wetted parts	Stainless steel 1.4305, Titanium

## ADDITIONAL DATA

Supply voltage dc max	32 V DC
Supply voltage dc min	9.6 V DC
Pressure rise	≤ 5,000 bar/s
Switching time	< 2 ms
Switching point adjustment range	2 ... 100 % of the nominal pressure range (Full Scale, FS), programmable at factory
Weight	80 g

## SAFETY & APPROVALS

IP class	IP67
Hysteresis	0.2...99.8 % of the nominal pressure range (Full Scale), programmable at factory
Shock resistance	500m / s <sup>2</sup> ; 11 ms half sine wave; DIN EN 60068-2-27
Vibration resistance	20g: 4..2000 Hz sine wave, DIN EN 60068-2-6
EMC	EMC 2014/30/EU, EN 61000-6-2:2005, EN 61000-6-3:2007
Accuracy	±0.5 % of the nominal pressure range (FS) at room temperature
Long term stability	±0.1 % of adjustment range (full scale) per year
Mechanical life expectancy	10,000,000 switching cycles at rise rates to 5,000 bar/s nominal pressure
Repeatability	±0.1 % full scale

