

ILLUMINATED TWIN TOUCH FLUSH

Illuminated

L61QH22A

Twintouch Illuminated Green Arrows Up Down

- IP66
- Flush pushbuttons
- Spring return
- Illuminate with LED blocks



PRODUCT DESCRIPTION

Illuminated flush twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip, contact blocks & LED module (must be in centre position) to make complete twin touch assembly. The central part of the head is translucent and illuminate according to the colour of LED block used.

Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Green / green
Function	Spring return
Illuminated	Yes
Impact resistance	IK05
IP class	IP66

Lens colour	Clear
Mechanical life expectancy	5 000 000 cycles
Recommended tightening torque	3
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Type	Twin touch flush