OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

ILLUMINATED TWIN TOUCH FLUSH

Illuminated

L61QH53
Twintouch Illuminated Flush White Black



- IP66
- Flush pushbuttons
- Spring return
- Illuminate with LED blocks

PRODUCT DESCRIPTION

Illuminated flush twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip, contact blocks & LED module (must be in centre position) to make complete twin touch assembly. The central part of the head is translucent and illuminate according to the colour of LED block used.

Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

TECHNICAL DATA

Type	Twin touch flush
Function	Spring return
Colour	White / black
Lens colour	Clear
Illuminated	Yes

IP class	IP66
Impact resistance	IK05
Temperature operational min	-25 °C

Temperature operational max	70 °C
Storage temperature min	-40 °C
Storage temperature max	70 °C
Mechanical life expectancy	5 000 000 cycles
Approvals	BV, CB, CE, CSA 22.2, UL 508
Recommended tightening torque	3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Climatic resistance - constant humid heat	IEC 60068-2-3

