OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# NON-ILLUMINATED TWIN TOUCH FLUSH

Non Illuminated

L61QA22N
Twintouch Flush Green Arrows Left Right



- IP66
- Flush pushbuttons
- Spring return
- Various colours & symbols

### PRODUCT DESCRIPTION

Non illuminated flush twin touch heads that mount in a 22.5mm hole with protection rating IP66

Combine with separate 333E clip and contact blocks to make complete twin touch assembly.
Available in various colour / text / symbol combinations.
All pushbuttons are spring return.

Supplied with a matt chrome bezel as standard.
For black plastic bezel change the part number from L61xxxx to L62xxxx.

Other colour / text / symbol combinations are possible please enquire for more details.

# TECHNICAL DATA

| | |
|---|---|
| **Type** | Twin touch flush |
| **Function** | Spring return |
| **Colour** | Green / green |
| **Illuminated** | No |

| | |
|---|---|
| **IP class** | IP66 |
| **Impact resistance** | IK05 |
| **Temperature operational min** | -25 °C |
| **Temperature operational max** | 70 °C |
| **Storage temperature min** | -40 °C |

| | |
|---|---|
| **Storage temperature max** | 70 °C |
| **Mechanical life expectancy** | 5 000 000 cycles |
| **Approvals** | BV, CB, CE, CSA 22.2, UL 508 |
| **Recommended tightening torque** | 3 |
| **Climatic resistance - cyclic damp heat** | IEC 60068-2-30 |
| **Climatic resistance - sea air** | IEC 60068-2-52 |
| **Climatic resistance - constant humid heat** | IEC 60068-2-3 |

