OEM Automatic Ltd
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CLIP & LED ASSEMBLY

Assembled single module clip & LED block

331EARL
LED Screw & Clip 24V ac/dc Red



- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head

PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block.
Combine with pilot light head to make complete pilot light assembly.
Available in colours red, green, yellow, white & blue.
Available in voltages 24V ac/dc, 115V ac & 230V ac.
Screw terminal connection.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Red
Connection type	Screw
Current consumption	25 mA ±20%
Frequency	50/60 Hz
LED supply voltage	12-24V ac/dc
LED voltage tolerance	± 20%
Lifetime at rated supply voltage (25°C)	100000 h
Protection rating rear of panel	IP20

Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	4 kV
Rated insulation voltage Ui	300 V
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Tightening torque max	1.2





