

## CLIP & LED ASSEMBLY

Assembled single module clip & LED block

331EAGL

LED Screw & Clip 24V ac/dc Green

- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head



### PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block.  
Combine with pilot light head to make complete pilot light assembly.  
Available in colours red, green, yellow, white & blue.  
Available in voltages 24V ac/dc, 115V ac & 230V ac.  
Screw terminal connection.

### TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Green
Connection type	Screw
Current consumption	25 mA $\pm$ 20%
Frequency	50/60 Hz
LED supply voltage	12-24V ac/dc
LED voltage tolerance	$\pm$ 20%
Lifetime at rated supply voltage (25°C)	50000 h
Protection rating rear of panel	IP20

Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)	4 kV
Rated insulation voltage Ui	300 V
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Tightening torque max	1.2

