

## CLIP & LED ASSEMBLY

Assembled single module clip & LED block

331EAWL  
LED Screw & Clip 24V ac/dc White

- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head



### PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block.  
Combine with pilot light head to make complete pilot light assembly.  
Available in colours red, green, yellow, white & blue.  
Available in voltages 24V ac/dc, 115V ac & 230V ac.  
Screw terminal connection.

### TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	White
Connection type	Screw
Current consumption	25 mA $\pm$ 20%
Frequency	50/60 Hz
LED supply voltage	12-24V ac/dc
LED voltage tolerance	$\pm$ 20%
Lifetime at rated supply voltage (25°C)	50000 h
Protection rating rear of panel	IP20

**Rated impulse withstand voltage Uimp  
(Overvoltage cat III - Pollution 3)**

4 kV

**Rated insulation voltage Ui**

300 V

**Storage temperature max**

70 °C

**Storage temperature min**

-40 °C

**Temperature operational max**

70 °C

**Temperature operational min**

-25 °C

**Tightening torque max**

1.2

