## **OEM Automatic Ltd**

Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

## **CLIP & LED ASSEMBLY**

Assembled single module clip & LED block

331EARM LED Screw & Clip 130V ac Red

- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head





## PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block.

Combine with pilot light head to make complete pilot light assembly.

Available in colours red, green, yellow, white & blue.

Available in voltages 24V ac/dc, 115V ac & 230V ac.

Screw terminal connection.

## **TECHNICAL DATA**

| Approvals                                 | UL 508, CSA 22.2, BV, CB, CE |
|---|------------------------------|
| Climatic resistance - constant humid heat | IEC 60068-2-3                |
| Climatic resistance - cyclic damp heat    | IEC 60068-2-30               |
| Climatic resistance - sea air             | IEC 60068-2-52               |
| Colour                                    | Red                          |
| Connection type                           | Screw                        |
| Current consumption                       | 20 mA ±10%                   |
| Frequency                                 | 50/60 Hz                     |
| LED supply voltage                        | 130 V AC                     |
| LED voltage tolerance                     | ± 10%                        |
| Lifetime at rated supply voltage (25°C)   | 100000 h                     |
| Protection rating rear of panel           | IP20                         |
|   |                              |

| Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3) | 4 kV   |
|--|--------|
| Rated insulation voltage Ui  | 300 V  |
| Storage temperature max  | 70 °C  |
| Storage temperature min  | -40 °C |
| Temperature operational max  | 70 °C  |
| Temperature operational min  | -25 °C |
| Tightening torque max  | 1.2    |
|  |        |

