

OEM Automatic Ltd Address: Whiteacres, Whetstone Leicester, LE8 6ZG 0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

CLIP & LED ASSEMBLY

Assembled single module clip & LED block

331EAWM LED Screw & Clip 130V ac White

- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head



BACO

PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block. Combine with pilot light head to make complete pilot light assembly. Available in colours red, green, yellow, white & blue. Available in voltages 24V ac/dc, 115V ac & 230V ac. Screw terminal connection.

TECHNICAL DATA

| Approvals | UL 508, CSA 22.2, BV, CB, CE |
|---|------------------------------|
| Climatic resistance - constant humid heat | IEC 60068-2-3 |
| Climatic resistance - cyclic damp heat | IEC 60068-2-30 |
| Climatic resistance - sea air | IEC 60068-2-52 |
| Colour | White |
| Connection type | Screw |
| Current consumption | 20 mA ±10% |
| Frequency | 50/60 Hz |
| LED supply voltage | 130 V AC |
| LED voltage tolerance | ± 10% |
| Lifetime at rated supply voltage (25°C) | 50000 h |
| Protection rating rear of panel | IP20 |

| Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3) | 4 kV |
|---|--------|
| Rated insulation voltage Ui | 300 V |
| Storage temperature max | 70 °C |
| Storage temperature min | -40 °C |
| Temperature operational max | 70 °C |
| Temperature operational min | -25 °C |
| Tightening torque max | 1.2 |





