

CLIP & LED ASSEMBLY

Assembled single module clip & LED block

331EAWH

LED Screw & Clip 230V ac White

- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head



PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block.
Combine with pilot light head to make complete pilot light assembly.
Available in colours red, green, yellow, white & blue.
Available in voltages 24V ac/dc, 115V ac & 230V ac.
Screw terminal connection.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	White
Connection type	Screw
Current consumption	16 mA \pm 30%
Frequency	50/60 Hz
LED supply voltage	230V ac
LED voltage tolerance	\pm 30%
Lifetime at rated supply voltage (25°C)	50000 h
Protection rating rear of panel	IP20

**Rated impulse withstand voltage Uimp
(Overvoltage cat III - Pollution 3)**

4 kV

Rated insulation voltage Ui

300 V

Storage temperature max

70 °C

Storage temperature min

-40 °C

Temperature operational max

70 °C

Temperature operational min

-25 °C

Tightening torque max

1.2

