**OEM Automatic Ltd**
Address: Whiteacres, Whetstone Leicester, LE8 6ZG
0116 284 9900 | Orders@oem.co.uk | www.oem.co.uk

# CLIP & LED ASSEMBLY

Assembled single module clip & LED block

331EAWH
LED Screw & Clip 230V ac White




- Screw terminals
- Long lifetime up to 100,000 hours
- 5 colour & voltage options
- For use with pilot light head

### PRODUCT DESCRIPTION

Pre assembled single module clip (331E) with LED block.
Combine with pilot light head to make complete pilot light assembly.
Available in colours red, green, yellow, white & blue.
Available in voltages 24V ac/dc, 115V ac & 230V ac.
Screw terminal connection.

## TECHNICAL DATA

| | |
|---|---|
| **Approvals** | UL 508, CSA 22.2, BV, CB, CE |
| **Climatic resistance - constant humid heat** | IEC 60068-2-3 |
| **Climatic resistance - cyclic damp heat** | IEC 60068-2-30 |
| **Climatic resistance - sea air** | IEC 60068-2-52 |
| **Colour** | White |
| **Connection type** | Screw |
| **Current consumption** | 16 mA ±30% |
| **Frequency** | 50/60 Hz |
| **LED supply voltage** | 230V ac |
| **LED voltage tolerance** | ± 30% |
| **Lifetime at rated supply voltage (25°C)** | 50000 h |
| **Protection rating rear of panel** | IP20 |

| | |
|---|---|
| **Rated impulse withstand voltage Uimp (Overvoltage cat III - Pollution 3)** | 4 kV |
| **Rated insulation voltage Ui** | 300 V |
| **Storage temperature max** | 70 °C |
| **Storage temperature min** | -40 °C |
| **Temperature operational max** | 70 °C |
| **Temperature operational min** | -25 °C |
| **Tightening torque max** | 1.2 |







