

CONTACT ASSEMBLIES

Clip, contact & LED combinations

333EAYH11

LED Screw 230V Yellow & Clip 1 x N/O & 1 x N/C

- Pre assembled clip, contact & LED blocks
- Many different combinations
- Simplified ordering



PRODUCT DESCRIPTION

Contact assemblies offer a more convenient and efficient way to purchase clips, contact & LED blocks.

If you know your required configuration it will save time and effort assembling them yourself and simplify the ordering process.

We have listed all of the most common options but if there is a combination missing you require then please contact us.

If you want the flexibility to configure yourself then please refer to the separate clips, contacts & LED blocks.

TECHNICAL DATA

Approvals	UL 508, CSA 22.2, BV, CB, CE
Climatic resistance - constant humid heat	IEC 60068-2-3
Climatic resistance - cyclic damp heat	IEC 60068-2-30
Climatic resistance - sea air	IEC 60068-2-52
Colour	Yellow
Connection solid wire max	2.5 mm ²
Connection stranded wire with ferrule max	1.5mm ²
Connection stranded wire with ferrule min	0.5mm ²
Connection type	Screw
Contact type	1 x N/O & 1 x N/C
Conventional free air thermal current Ith (AC15)	10 A
Frequency	50/60 Hz
LED supply voltage	230V ac

Protection rating rear of panel	IP20
Recommended tightening torque	1.2
Storage temperature max	70 °C
Storage temperature min	-40 °C
Temperature operational max	70 °C
Temperature operational min	-25 °C
Tightening torque max	1.2

